

# QuickSpecs **HPE Aruba Networking 580EX Series Hazardous Location Access Points**

---

## Overview

**Shape the Future of QuickSpecs – Your Input Matters**

### **HPE Aruba Networking 580EX Series Hazardous Location Access Points**

#### **Flagship Wi-Fi 6 performance and flexible options for challenging outdoor environments**

Purpose-built to survive the harshest outdoor and hazardous indoor environments, the HPE Aruba Networking 580EX Series Hazardous Location Access Points withstand exposure to extreme high and low temperatures and persistent moisture, are fully sealed to keep out airborne contaminants, and include industrial surge protection. The 580EX series offers flexible power and management options to meet the needs of diverse environments and can be deployed using existing mounts. Like all HPE Aruba Networking access points, the 580EX series is Wi-Fi 6 certified and backed by a limited lifetime warranty.

---



**HPE Aruba Networking 580EX Series Hazardous Location Access Points**

---

## Overview

### Key Features

- Weatherproofed and temperature hardened with HazLoc Class 1 Division 2, ATEX Zone 2 certification, and IP66 rating to support the harshest outdoor environments
  - Wi-Fi 6 support for UL and DL MU-MIMO and OFDMA
  - More power with 5 Gbps SmartRate Ethernet port
  - High power Bluetooth and 802.15.4/Zigbee radios to meet Industrial IoT requirements
  - Backed by HPE Aruba Networking's Limited Lifetime Warranty for peace of mind
- 



## Standard Features

### Designed for Outdoor Flexibility

HPE Aruba Networking 580EX Series Hazardous Location Access Points are weatherproofed and temperature hardened to support hazardous indoor and outdoor environments, including outdoor oil rigs, industrial manufacturing, and transportation sites. With Wi-Fi 6 capabilities, high power Bluetooth and 802.15.4/Zigbee radios, and maximum aggregate throughput of 2.97 Gbps, 580EX series access points deliver the speed and reliability needed for demanding Industrial IoT environments.

To support high-performance connectivity in dense mobile and IoT outdoor environments, 580EX series access points deliver maximum aggregate on air data rates of 2.97 Gbps and include 5 Gbps Smart Rate Ethernet ports. In addition, dual redundant power/port failover and support for AC ensure high availability with uninterrupted performance.

---

### Wi-Fi 6 Benefits

HPE Aruba Networking 580EX Series Hazardous Location Access Points are based on the Wi-Fi 6/802.11ax standard, which means that Wi-Fi 6 features such as Uplink and Downlink Orthogonal Frequency Division Multiple Access (OFDMA), BSS coloring, Downlink Multi-User MIMO (MU-MIMO), and cellular co-location are fully supported making it more efficient and secure.

### Advantages of OFDMA

This capability allows HPE Aruba Networking access points to handle multiple 802.11ax capable clients on each channel simultaneously, regardless of device or traffic type. Channel utilization is optimized by handling each transaction via smaller sub-carriers or resource units (RUs), which means that clients are sharing a channel and not competing for airtime and bandwidth.

### Bi-directional Multi-User MIMO (MU-MIMO)

Similar to downlink MU-MIMO in Wi-Fi 5 (802.11ac Wave 2), 580EX series access points can simultaneously connect clients using downlink—and now—uplink spatial streams. The added benefit is the ability to multiply the number of clients that can now send traffic, thus optimizing client-to-access point spatial stream diversity.

---

### Wi-Fi Optimization

#### Client optimization

HPE Aruba Networking's patented AI-powered ClientMatch technology eliminates sticky client issues by steering a client to the access point where it receives the best radio signal. ClientMatch also dynamically steers traffic to load balance access points to improve the user experience.

#### Automated Wi-Fi radio frequency management

To optimize the user experience and provide greater stability, HPE Aruba Networking AirMatch allows organizations to automate network optimization using machine learning. AirMatch provides dynamic bandwidth adjustments to support changing device density and enhanced roaming using an even distribution of Effective Isotropic Radiated Power (EIRP) to radios, and real-time channel assignments to mitigate co-channel interference.

#### Intelligent Power Monitoring (IPM)

HPE Aruba Networking 580EX Series access points continuously monitor and report hardware energy consumption and temperature. access points can be configured to enable or disable capabilities based on the available PoE power—ideal when wired switches have exhausted their power budget. Additionally, with IPM, if the access point gets too close to the maximum temperature limit, it can disable features to prevent overheating.

#### HPE Aruba Networking Advanced Cellular Coexistence (ACC)

Unique to HPE Aruba Networking, Advanced Cellular Coexistence uses built-in filtering to automatically minimize the impact of interference from cellular networks, distributed antenna systems (DAS), and commercial small cell or femtocell equipment.

---

### IoT Capabilities

#### High power Bluetooth and Zigbee

The 580EX series was the first HPE Aruba Networking access point to feature a high-powered Bluetooth and 802.15.4/Zigbee radio, ensuring maximum range and performance for IoT applications. Built in Bluetooth and Zigbee capabilities simplifies deploying and managing IoT-based location services, asset tracking services, security solutions and IoT sensors and allows



## Standard Features

organizations to leverage the 580EX Series as an IoT platform. There is no need for an overlay infrastructure or additional IT resources.

### **Advanced IoT Coexistence (AIC)**

Built-in filtering allows Wi-Fi and Bluetooth/Zigbee radios to operate at maximum capacity without the impact of interference.

### **Target Wake Time (TWT)**

Ideal for IoT solutions that communicate infrequently, this Wi-Fi 6 capability allows IoT devices to use 802.11ax protocol. TWT coordinates with client IoT devices to allow them to sleep for extended periods and use shorter wake times to communicate before returning to sleep. This substantially extends the useful operating life of Wi-Fi 6 based, battery-powered sensors.

---

## **HPE Aruba Networking secure infrastructure**

The HPE Aruba Networking 580EX Series is an integral part of HPE Aruba Networking's SASE and Zero Trust security approach to help protect user authentication and wireless traffic. Select capabilities include:

### **WPA3 and Enhanced Open**

With the introduction of WPA3 and Enhanced Open, a Wi-Fi 6 certified client will never send unencrypted traffic over the air. Even with an open authenticated network, Enhanced Open still provides strong encryption over the air. In all Wi-Fi 6 user sessions, each user is uniquely encrypted and if they disconnect and reconnect, the encryption changes from session to session.

### **WPA2-MPSK**

MPSK enables simpler passkey management for WPA2 devices—should the Wi-Fi password on one device change, no additional changes are needed for other devices. This feature is enabled when networks are deployed with HPE Aruba Networking NAC.

---

## **Simple and Secure Access**

To improve security and ease of management, IT can centrally configure and automatically enforce role-based policies that define proper access privileges for employees, guests, contractors, and other user groups—no matter where users connect on wired and wireless networks. Dynamic Segmentation eliminates the time consuming and error-prone task of managing complex and static VLANs, ACLs, and subnets by dynamically assigning policies and keeping traffic secure and separated.

---

## **Flexible Operation and Management**

Our unified access points can operate as standalone access points or with a gateway for greater scalability, security, and manageability. Access points can be deployed using zero touch provisioning—without on-site technical expertise—for ease of implementation. HPE Aruba Networking access points can be managed using cloud-based or on-premises solutions for any campus, branch, or remote work environment. HPE Aruba Networking Central provides a single pane of glass for overseeing every aspect of wired and wireless LANs, WANs, and VPNs. AI-powered analytics, end-to-end orchestration and automation, and advanced security features are built natively into the solution.

---

## **Additional Wi-Fi features**

### **Transmit Beamforming (TxBF)**

Increased signal reliability and range

### **Dynamic Frequency Selection (DFS)**

Optimized use of available RF spectrum

### **Maximal Ratio Combining (MRC)**

Improved receiver performance for multi antenna access points.

### **Cyclic Delay/Shift Diversity (CDD/CSD)**

Enable use of multiple transmit antennas

### **Space-Time Block Coding (STBC)**

Increased connection robustness

### **Low-Density Parity Check (LDPC)**

High performance error detection and correction coding for enhanced receiver performance.

---



## Configuration Information

### BTO Models

#### 580EX Unified HazLoc Access Points

Rule #	Description	SKU
2	HPE Aruba Networking AP-585EX (US) Dual Radio 4x4 802.11ax Internal Omni Ants Unified HazLoc AP	R7T29A
1	HPE Aruba Networking AP-585EX (RW) Dual Radio 4x4 802.11ax Internal Omni Ants Unified HazLoc AP	R7T30A
3	HPE Aruba Networking AP-585EX (EG) Dual Radio 4x4 802.11ax Internal Omni Ants Unified HazLoc AP	R7T31A
4	HPE Aruba Networking AP-585EX (IL) Dual Radio 4x4 802.11ax Internal Omni Ants Unified HazLoc AP	R7T32A
5	HPE Aruba Networking AP-585EX (JP) Dual Radio 4x4 802.11ax Internal Omni Ants Unified HazLoc AP	R7T33A
6	HPE Aruba Networking AP-585EX (ID) Dual Radio 4x4 802.11ax Internal Omni Antennas HazLoc AP	S5E01A
2	HPE Aruba Networking AP-587EX (US) Dual Radio 4x4 Wi-Fi 6 Internal Directional HazLoc Access Point	R7T34A
1	HPE Aruba Networking AP-587EX (RW) Dual Radio 4x4 Wi-Fi 6 Internal Directional HazLoc Access Point	R7T35A
3	HPE Aruba Networking AP-587EX (EG) Dual Radio 4x4 Wi-Fi 6 Internal Directional HazLoc Access Point	R7T36A
4	HPE Aruba Networking AP-587EX (IL) Dual Radio 4x4 Wi-Fi 6 Internal Directional HazLoc Access Point	R7T37A
5	HPE Aruba Networking AP-587EX (JP) Dual Radio 4x4 Wi-Fi 6 Internal Directional HazLoc Access Point	R7T38A
6	HPE Aruba Networking AP-587EX (ID) Dual Radio 4x4 802.11ax Internal Directional Ants HazLoc AP	S5E02A

#### Configuration Rules

Rule #	Description
1	Available everywhere except US, Israel, Egypt, Indonesia and Japan. Partners must have an SOT (Cross border agreement).
2	Available in US only. Partners must have an SOT (Cross border agreement).
3	Available in Egypt only. Partners must have an SOT (Cross border agreement).
4	Available in Israel only. Partners must have an SOT (Cross border agreement).
5	Available in Japan only. Partners must have an SOT (Cross border agreement).
6	Available in Indonesia only. Partners must have an SOT (Cross border agreement).

**Notes:** OCA Only Model Selection Form - HPE Aruba Networking > Wireless > Access Points > Outdoor / Rugged: HPE Aruba Networking 580EX Series Hazardous Location Access Points

### Mounting Accessories

#### AP Mount Kits

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Rule #	Description	SKU
	HPE Aruba Networking AP-270-MNT-V1 Outdoor AP Long Arm Pole/Wall Mounting Bracket	JW052A
	HPE Aruba Networking AP-270-MNT-H1 Outdoor AP Hanging One-Way Tilt Pole/Wall Mounting Bracket	JW054A
	HPE Aruba Networking AP-270-MNT-H2 Outdoor AP Flush Wall Mounting Bracket	JW055A
	HPE Aruba Networking AP-270-MNT-H3 Outdoor AP Hanging Dual-Tilt Pole/Wall Mounting Bracket	R6W11A

- Notes:**
- For all AP-580EX models, the AP-270-MNT-V2 mounting bracket is not compatible with any AP-580 models
  - For 585EX:
    - V1 bracket most often used for pole mount.
    - H1 bracket most often used for hanging from inclined or horizontal structure.
    - The AP-585EX chassis does not ship with bracket
  - For 587EX:
    - H1 bracket most often with AP-587EX for mounting to a wall. Allows chassis tilt.
    - V1 brackets can be used but will result in the AP-587EX pointing down.
    - The AP-587EX chassis does not ship with bracket.



## Configuration Information

### Power Options

#### PoE Power Options

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Rule #	Description	SKU
1	HPE Aruba Networking AP-POE-BTSR 1-Port Smart Rate 802.3bt 60W Midspan Injector <ul style="list-style-type: none"> <li>Add AC power cord, Unrestricted</li> </ul>	R1C73A
	HPE Aruba Networking PD-9501-5GCO-AC 60W 802.3bt Smart Rate Otdr Surge Protection Midspan Injector	R7T40A
	HPE Aruba Networking PD-9501-5GCO-DC 60W 802.3bt Smart Rate Otdr Surge Protection Midspan Injector	R7T41A

#### Configuration Rules

Rule #	Description
1	If this Power Injector is selected, bring in (Min 1 // Max 1) Localized power cord based on the HPE Aruba Networking Localization Menu

- Notes:**
- Indoor Injector provides no surge protection
  - Indoor injector requires indoor AC power cord  
AP-58XEX may be powered by PoE Only
  - The listed power injectors are not HazLoc certified and must be located outside of classified areas
  - R7T40A and R7T41A do not include a power cord, power cord must be constructed by installer using the included power connector parts and assembled per the user guide by a certified installer

#### Power Injector Mounts

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Rule #	Description	SKU
	HPE Aruba Networking PD-MOUNT-OD Outdoor PoE Midspan Injectors Pole/Mast Mount Kit	JW620A

**Notes:** This is optional but recommended for outdoor injectors R7T40A and R7T41A

#### Power Cable Kit

Std (Min 0 // max 1) User Selection (min 0 // max 1)

Rule #	Description	SKU
	HPE Aruba Networking Outdoor AP-AC-MLX-EX Outdoor Molex AC Power Connector Kit	R9E56A

**Notes:** The AP-AC-MLX-EX is an assembly kit including a HazLoc compliant cable gland, power cable type is installer supplied, should use outdoor rated, UV stabilized AC power cable. Check the installation guide for more details. Any site-specific HazLoc requirements may require additional 3rd party components.

### Transceivers

#### SFP/SFP+

Rule #	Description	SKU
	HPE Aruba Networking 1G Ind-Temp SFP LC SX 500m MMF Transceiver	JL780A
	HPE Aruba Networking 1G Ind-Temp SFP LC LX 10km SMF Transceiver	JL781A
	HPE Aruba Networking 10G Ind-Temp SFP+ LC SR 300m MMF Transceiver	JL782A
	HPE Aruba Networking 10G Ind-Temp SFP+ LC LR 10km SMF Transceiver	JL783A
	HPE Aruba Networking CKIT-EX-OD-SFP Outdoor HazLoc SFP Fiber Strain Relief	R7L09A

**Notes:** R7L09A is required if using SFP or SFP+ on AP-580EX.



## Configuration Information

### Accessories

#### Spare Items

Std (Min 0 // max 99) User Selection (min 0 // max 99)

Rule #	Description	SKU
1	HPE Aruba Networking Otdr AP Covers/Glands 1pk M25/5pk M20 Cover and Gland/2pk M16 Cover Ground Kit	Q8N47A

#### Configuration Rules

Rule #	Description	SKU
1	This is a collection of extra covers and cabling glands, replicating what is in the shipping box	
<b>Notes:</b> Spares of items that are shipped with the AP-580EX chassis. Note this does NOT include HazLoc certified glands. If HazLoc certified glands are required, they must be purchased by 3rd party.		

### Software

#### Central

##### Cloud Services / Access Point Foundation Subscriptions

2, 8	HPE Aruba Networking Central AP Foundation 1-year Subscription E-STU	Q9Y58AAE
2, 8	HPE Aruba Networking Central AP Foundation 3 year Subscription E-STU	Q9Y59AAE
2, 8	HPE Aruba Networking Central AP Foundation 5 year Subscription E-STU	Q9Y60AAE
2, 8	HPE Aruba Networking Central AP Foundation 7 year Subscription E-STU	Q9Y61AAE
2, 8	HPE Aruba Networking Central AP Foundation 10 year Subscription E-STU	Q9Y62AAE

##### Cloud Services / Access Point Advanced Subscriptions

2, 8	HPE Aruba Networking Central AP Advanced 1 year Subscription E-STU	Q9Y63AAE
2, 8	HPE Aruba Networking Central AP Advanced 3 year Subscription E-STU	Q9Y64AAE
2, 8	HPE Aruba Networking Central AP Advanced 5 year Subscription E-STU	Q9Y65AAE
2, 8	HPE Aruba Networking Central AP Advanced 7 year Subscription E-STU	Q9Y66AAE
2, 8	HPE Aruba Networking Central AP Advanced 10 year Subscription E-STU	Q9Y67AAE

##### On-Prem Services / Access Point Foundation Subscriptions

3, 8	HPE Aruba Networking Central on Prem AP Foundation 1 year Subscription E-STU	R6U63AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 3 year Subscription E-STU	R6U64AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 5 year Subscription E-STU	R6U65AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 7 year Subscription E-STU	R6U66AAE
3, 8	HPE Aruba Networking Central on Prem AP Foundation 10 year Subscription E-STU	R6U67AAE

##### On-Prem Services / Access Point Foundation Government Subscriptions

3	HPE Aruba Networking COP AP Foundation Government 1-year Subscription E-STU	S1P56AAE
3	HPE Aruba Networking COP AP Foundation Government 3-year Subscription E-STU	S1P57AAE
3	HPE Aruba Networking COP AP Foundation Government 5-year Subscription E-STU	S1P58AAE
3	HPE Aruba Networking COP AP Foundation 7-year Government Subscription E-STU	S1P59AAE
3	HPE Aruba Networking COP AP Foundation 10-year Government Subscription E-STU	S1P60AAE

#### Configuration Rules

Rule #	Description	SKU
2	Add the Central Cloud Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > Cloud Services	
3	Add the Central On-Prem Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > On-Prem Services	
6	Add the Central FedRAMP Service Skus to the HPE Aruba Networking Catalog as Standalone: HPE Aruba Networking > Network Management > Central > FedRAMP	



## Configuration Information

8	For OCA: When configuring the following AP 10-Pack, selection condition for this Subscription should be 0(default) or 10	
	HPE Aruba Networking AP-503 (RW) 10-Pack Dual Radio 2x2:2 Wi-Fi 6 Campus Access Point	S1E83A
	HPE Aruba Networking AP-503 (US) 10-Pack Dual Radio 2x2:2 Wi-Fi 6 Campus Access Point	S1E84A

### As-a-Service

#### Cloud Services / Access Point Foundation Subscriptions

7	HPE Aruba Networking Central AP Foundation 1 year Subscription SaaS	Q9Y58AAS
7	HPE Aruba Networking Central AP Foundation 3 year Subscription SaaS	Q9Y59AAS
7	HPE Aruba Networking Central AP Foundation 5 year Subscription SaaS	Q9Y60AAS
7	HPE Aruba Networking Central AP Foundation 7 year Subscription SaaS	Q9Y61AAS
7	HPE Aruba Networking Central AP Foundation 10 year Subscription SaaS	Q9Y62AAS

#### Cloud Services / Access Point Advanced Subscriptions

7	HPE Aruba Networking Central AP Advanced 1 year Subscription SaaS	Q9Y63AAS
7	HPE Aruba Networking Central AP Advanced 3 year Subscription SaaS	Q9Y64AAS
7	HPE Aruba Networking Central AP Advanced 5 year Subscription SaaS	Q9Y65AAS
7	HPE Aruba Networking Central AP Advanced 7 year Subscription SaaS	Q9Y66AAS
7	HPE Aruba Networking Central AP Advanced 10 year Subscription SaaS	Q9Y67AAS

#### Configuration Rules

Rule#	Description	SKU
7	For IRIS reference only. No action required for OCX and Clic	



## Technical Specifications

### Hardware Variants

- AP-585EX
  - Built in omni-directional antennas (H and V polarized)
  - 5Ghz Antennas 4.5dBi uncorrelated avg (5.8dBi peak)
  - 2.4GHz Antennas 3.0dBi uncorrelated avg (4.4dBi peak)
  - Bluetooth Antenna 4.8dBi peak
- AP-587EX
  - Built in directional antennas (H, V, and +/-45 polarized)
  - 5Ghz Antennas 5.2dBi uncorrelated avg (6.6dBi peak)
  - 2.4Ghz Antennas 5.7dBi uncorrelated (5.8dBi peak)
  - Bluetooth Antenna 6.3dBi peak

### Wi-Fi Radio Specifications

- AP type: Outdoor Hardened, Wi-Fi 6 dual radio, 5 GHz and 2.4 GHz 802.11ax 4x4 MIMO
- 5 GHz radio: Four spatial stream Single User (SU) MIMO for up to 2.4 Gbps wireless data rate with individual 4SS HE80 (or 2SS HE160) 802.11ax client devices, or with four 1SS or two 2SS HE80 802.11ax MU-MIMO capable client devices simultaneously
- 2.4 GHz radio: Four spatial stream Single User (SU) MIMO for up to 1,150 Mbps wireless data rate with individual 4SS HE40 802.11ax client devices or with two 2SS HE40 802.11ax MU-MIMO capable client devices simultaneously
- Support for up to 1,024 associated client devices per radio (typical recommended limit for active outdoor clients is 100-200 depending on distance), and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
  - 2.400 to 2.4835GHz
  - 5.150 to 5.250GHz
  - 5.250 to 5.350GHz
  - 5.470 to 5.725GHz
  - 5.725 to 5.850GHz
- Available channels: Dependent on configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
  - 802.11b: Direct-sequence spread-spectrum (DSSS)
  - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
  - 802.11ax: Orthogonal frequency-division multiple access (OFDMA) with up to 37 resource units (for an 80 MHz channel)
- Supported modulation types:
  - 802.11b: BPSK, QPSK, CCK
  - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM (proprietary extension)
  - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM (proprietary extension)
  - 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
- 802.11n high-throughput (HT) support: HT20/40
- 802.11ac very high throughput (VHT) support: VHT20/40/80/160
- 802.11ax high efficiency (HE) support: HE20/40/80/160
- Supported data rates (Mbps):
  - 802.11b: 1, 2, 5.5, 11
  - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54
  - 802.11n: 6.5 to 600 (MCS0 to MCS31, HT20 to HT40), 800 with 256-QAM
  - 802.11ac: 6.5 to 1,733 (MCS0 to MCS9, NSS = 1 to 4, VHT20 to VHT160), 2,166 with 1024-QAM
  - 802.11ax (2.4GHz): 3.6 to 1,147 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE40)
  - 802.11ax (5GHz): 3.6 to 2,402 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE160)
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU



## Technical Specifications

- Transmit power: Configurable in increments of 0.5 dBm
  - Maximum (aggregate, conducted total) transmit power (limited by local regulatory requirements):
    - 2.4 GHz band: +29 dBm (23dBm per chain)
    - 5 GHz band: +28 dBm (22 dBm per chain)
    - Hazardous Location APs do not exceed 33dBm total EIRP to stay under the ATEX Zone 2 intrinsic safety limits
- Notes: conducted transmit power levels exclude antenna gain. For total (EIRP) transmit power, add antenna gain.**
- Advanced Cellular Coexistence (ACC) minimizes the impact of interference from cellular networks
  - Maximum ratio combining (MRC) for improved receiver performance
  - Cyclic delay/shift diversity (CDD/CSD) for improved downlink RF performance
  - Space-time block coding (STBC) for increased range and improved reception
  - Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
  - Transmit beam-forming (TxBF) for increased signal reliability and range
  - 802.11ax Target Wait Time (TWT) to support low-power client devices
  - Advanced IoT Existence (AIC) allows for concurrent operation of the IoT and 2.4Ghz radios without issue
- 

## Wi-Fi Antennas

- AP-585EX: Four integrated dual-band omni-directional antennas for 4x4 MIMO with peak antenna gain of 4.4dBi in 2.4GHz and 5.8dBi in 5GHz. Built-in antennas are optimized for a horizontally mounted orientation of the AP. The downtilt angle for maximum gain is roughly 10 degrees.
    - A mix of horizontally and vertically polarized antenna elements are used
    - Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 3.0dBi in 2.4GHz and 4.5dBi in 5GHz.
  - AP-587EX: Four integrated dual-band directional antennas for 4x4 MIMO with peak antenna gain of 5.8dBi in 2.4GHz and 6.6dBi in 5Ghz. Built-in antennas are optimized for a vertically oriented installation to a wall or pole.
    - A mix of horizontal, vertical, and +/-45 degree antenna elements are used
    - Combining the patterns of each of the antennas of the MIMO radios, the peak gain of the combined, average pattern is 5.7dBi in 2.4Ghz, and 5.2dBi in 5Ghz
- 

## Other Interfaces

- Wired network interface (E0)
  - 100/1000/2500/5000Base-T Ethernet
  - 5Gbps Smart Rate: NBase-T, 802.3bz
  - PoE PD support on E0
  - IEEE/802.3az support
  - Support for jumbo frames (MTU up to 9,216 bytes)
- Wired network interface (E1)
  - 10GBASE-R SFP+ port
  - IEEE/802.3az support (as applicable)
  - Support for jumbo frames (up to 9,216 bytes)
  - 1 x SFP+ cage
  - When used in operation it is expected that this is the primary uplink port
  - Only recommended industrial temperature SFP/SFP+ modules should be used for optimal performance
- Wired network interface (E2)
  - 10/100/1000BaseT Ethernet
  - IEEE/802.3az support (as applicable)
  - Support for jumbo frames (up to 9,216 bytes)
  - Support for PoE PSE of at 802.3at (preferable to possibly be able to reach 802.3at PSE with IPTM policy if needed)
- AC power interface: 110-240V (requires AP-AC-MLX power connector kit)



## Technical Specifications

- Bluetooth (BLE5.0) and Zigbee (802.15.4) radio
  - BT: up to 8dBm transmit power (class 2) and -98dBm receive sensitivity (125kbps)
  - Zigbee: up to 8dBm transmit power and -96dBm receive sensitivity
- Visual indicators (multi-color LED): for System and Radio status
- GNSS L1 (1575.42 MHz) receiver supporting GPS, Galileo, GLONASS, and BeiDou signal
  - Receive sensitivity: -163dBm (tracking)
  - Integrated antenna with gain of ~2dBi
- Reset button: factory reset, LED mode control (normal/off)
- USB-C console interface
- Shielded Twisted Pair (STP) Ethernet cable should be used on all Ethernet interfaces for proper surge protection

---

## Power Sources and Power Consumption

- The access point supports direct AC power and Power over Ethernet (802.3bt POE; on port E0 only)
- When both AC and POE power sources are available, AC power takes priority over POE
- Power sources are sold separately; see the ordering Information section below for details
- See below conditions for each power configuration:
  - When powered by AC, the access point will operate without restrictions, including 802.3af/at support (with upper thermal limitations).\* With IPTM enabled, the access point will adjust power requirements to meet requirements, and will reduce according to established IPTM policy
  - When powered by 802.3bt Class 6, the access point will operate without restriction, limited to 802.3af PSE support.\* With IPTM enabled, the access point will adjust power requirements to meet requirements, and will reduce according to established IPTM policy
  - When powered by 802.3bt Class 5 with LLDP, full function but no PSE support\*
  - When powered by 802.3at, access point will reduce 2.4Ghz to 1 chain, and will reduce the 5Ghz to 3 chains, no PsE out\*
  - When powered by 802.3af, the access point will boot up, but not enable any radios, regardless of IPTM settings.
- **Notes:**\*With IPTM enabled, the AP will adjust power requirements to meet requirements, and will reduce power as necessary according to the established IPTM policy
- Maximum (worst-case) power consumption:
  - AC powered: 71W (802.3af/at\*)
  - POE powered (802.3bt Class 6): 49.5W (802.3af PSE only)
  - POE powered (802.3bt Class 5): 35.5W (no PSE)
  - POE powered (802.3at, IPM disabled): 25.5W (1 chain @ 2.4Ghz, 3 chains @ 5Ghz, no PSE)
- Maximum (worst-case) power consumption in idle mode: 9.2W (POE) or 10.8W (AC)
- Maximum (worst-case) power consumption in deep-sleep mode: 3.0W (POE) or 4.4W (AC)

---

## Mounting Details

- Optional mounting kits:
  - AP-OUT-MNT-V1A – Long arm wall or pole mounting bracket
  - AP-270-MNT-H1 – Single-tilt mounting bracket for wall or ceiling
  - AP-270-MNT-H2 – Flush ceiling or wall mounting bracket
  - AP-270-MNT-H3 – Dual-tilt mounting bracket for wall or ceiling



## Technical Specifications

### Mechanical Specifications

#### AP-585EX

- Dimensions/weight (AP-585EX unit only):
  - 324mm (W) x 313mm (D) x 320mm (H) / 12.6" (W) x 12.3" (D) x 9.6" (H)
  - 5.24kg / 11.5lbs
- Dimensions/weight (AP-585EX shipping pkg, no mount):
  - 431mm (W) x 415mm (D) x 442mm (H) / 17" (W) x 16.3" (D) x 17.4" (H)
  - 7.81kg / 17.2lbs

#### AP-587EX

- Dimensions/weight (AP-587EX unit only):
  - 302mm (W) x 300mm (D) x 174mm (H) / 5.9" (W) x 11.8" (D) x 6.9" (H)
  - 4.51kg / 9.9lbs
- Dimensions/weight (AP-587EX shipping pkg, no mount):
  - 385mm (W) x 272mm (D) x 433mm (H) / 15.2" (W) x 10.7" (D) x 17" (H)
  - 6.03kg / 13.3lbs

---

### Environmental Specifications

- Operating conditions
  - Temperature: -40C to +65C / -40F to +149F with full solar loading
  - Humidity: 5% to 93% non-condensing internal
  - Rated for operation in all weather conditions
- Storage and transportation conditions
  - Temperature: -40C to +70C / -40F to +158F.
- Operating Altitude: 3000m
- Water and Dust
  - IP66
- Salt Tolerance
  - Test to ASTM B117-07A Salt Spray 200hrs
- Wind Survival: 150mph (GR-487)

---

### Reliability

Mean Time Between Failure (MTBF): 828,651hrs (~95yrs) at +25C operating temperature.

---

### Regulatory Compliance

- FCC/ISED
- CE Marked
- RED Directive 2014/53/EU
- EMC Directive 2014/30/EU
- Low Voltage Directive 2014/35/EU
- UL/IEC/EN 60950-1
- IEC 60950-22
- UL/IEC/EN 62368-1
- IEC/EN60601-1-2
- EN 50155
- EN IEC 60079-0
- EN IEC 60079-7
- IEC 60079-0
- IEC 60079-7
- CSA C22.2 No.213-17



## Technical Specifications

- UL 121201
- UL 50E

For more country-specific regulatory information and approvals, please see your HPE Aruba Networking representative.

---

## Regulatory Model Numbers

- AP-585EX: APEX0585
  - AP-587EX: APEX0587
- 

## Certifications

- Wi-Fi Alliance:
  - Bluetooth SIG
  - Ethernet Alliance (E0, PoE PD device, class 6; E2, PoE PSE device, class 3)
  - Class 1 Div 2
  - ATEX Zone 2
  - IECEX
- 

## Warranty

HPE Aruba Networking's hardware limited lifetime warranty

---

## Minimum Operating System Software Versions

- HPE Aruba Networking Wireless Operating System Networking InstantOS 8.10.0.1
  - HPE Aruba Networking Wireless Operating System 10.4.0.0
- 



## Technical Specifications

RF Performance Table		
Band / Rate	Maximum Transmit Power (dBm) per transmit chain	Receiver Sensitivity (dBm) per receive chain
<b>2.4Ghz, 802.11b</b>		
1Mbps	23	-95
11Mbps	23	-87
<b>2.4Ghz, 802.11g</b>		
6Mbps	23	-92
54 Mbps	20	-74
<b>2.4Ghz, 802.11n/ac HT20</b>		
MCS0	23	-92
MCS8	18	-70
<b>2.4Ghz, 802.11n/ac HT40</b>		
MCS0	23	-89
MCS9	18	-66
<b>2.4Ghz, 802.11 ax HE20</b>		
MCS0	23	-92
MCS11	16	-62
<b>2.4Ghz, 802.11 ax HE40</b>		
MCS0	23	-89
MCS11	16	-59
<b>5Ghz, 802.11a</b>		
6Mbps	22	-93
54Mbps	22	-75
<b>5Ghz, 802.11n/ac HT20</b>		
MCS0	22	-93
MCS8	20	-71
<b>5Ghz, 802.11n/ac HT40</b>		
MCS0	22	-90
MCS9	20	-65
<b>5Ghz, 802.11n/ac HT80</b>		
MCS0	22	-87
MCS9	20	-62
<b>5Ghz, 802.11ax HE20</b>		
MCS0	22	-93
MCS11	18	-62
<b>5Ghz, 802.11ax HE40</b>		
MCS0	22	-90
MCS11	18	-59
<b>5Ghz, 802.11ax HE80</b>		
MCS0	22	-87
MCS11	18	-56

**Notes:** Maximum capability of the hardware provided (excluding antenna gain). Maximum transmit power is limited by local regulatory settings.




## Summary of Changes


Date	Version History	Action	Description of Change
28-Jul-2025	<b><u>Version 9</u></b>	Changed	Update survey link.
07-Apr-2025	<b><u>Version 8</u></b>	Changed	Overview, Standard Features, Configuration Information, and Technical Specifications sections were updated.
21-Jan-2025	<b><u>Version 7</u></b>	Changed	QuickSpecs was updated.
16-Dec-2024	<b><u>Version 6</u></b>	Changed	QuickSpecs was updated.
04-Dec-2023	<b><u>Version 5</u></b>	Changed	Series name was updated.
16-Oct-2023	<b><u>Version 4</u></b>	Changed	Configuration Information section was updated
07-Aug-2023	<b><u>Version 3</u></b>	Changed	Configuration Information section was updated.
05-Jul-2022	<b><u>Version 2</u></b>	Changed	Configuration Information section was updated.
04-Apr-2022	<b><u>Version 1</u></b>	New	New QuickSpecs



## Copyright

Make the right purchase decision.  
Contact our presales specialists.

 Chat now (sales)

 Call now

 Get updates

**Shape the Future of QuickSpecs – Your Input Matters**

---

© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a50004276enw - 16880 - Worldwide - V9 - 28-July-2025

