



Coiled USB-A to USB-C Charging Cable

USB Type-A Male to Type-C Male, 1 m (3 ft.) Tangle-Resistant Curly Design, Angled Plugs, No Data Transmission, Black

Part No.: **356220**

EAN-13: 0766623356220 | UPC: 766623356220

Coiled USB Cable - USB-A Male to USB-C Male - the ideal charging cord to keep car chargers, charging cabinets, and charging carts clutter-free

Make your charging cable management clutter-free with the coiled, tangle-resistant USB-A to USB-C Charging Cable from Manhattan. It flexibly stretches to just the right length you need without tangles and retracts back to a compact format for easy handling and storage. For even more convenience, both plugs are 90° angled for easy connection in places like tight corners or hard-to-reach ports. The reversible USB-C connector will always fit, no matter which way you insert the cable.

Features:

- USB-A male to USB-C male for charging a USB-C device from a USB-A port
- Does not support data transmission
- Curly, retracting design to eliminate annoying cable tangles and clutter
- Ideal for Manhattan charging cabinets, charging carts and car chargers
- Expands from compact 35 cm (14 in.) to extended 1 m (3 ft.)
- Convenient 90° angled plugs for easy connection in inconvenient places like tight corners or hard-to-reach ports
- Charges a USB-C powered device such as a smartphone, tablet, GPS, PS5 controller, Bluetooth® headphones, and more

- Pure bare copper wire for maximum conductivity
- Corrosion-resistant contacts
- Flexible, durable PVC jacket
- Supports current up to 3 A
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- UL 20233
- REACH

General

- One USB-C 24-pin male
- One USB-A 4-pin male
- Nickel-plated contacts
- Wire: pure bare copper
- PVC boot
- 24/30 AWG
- Length: 35 cm (14 in.) to 1 m (3 ft.) max.
- Outer diameter (OD): 3.5 mm (0.14 in.)
- Net weight: 22 g (0.78 oz.)
- Gross weight: 24 g (0.85 oz.)

Electrical

- Withstanding voltage: 300 VDC 10 ms
- Insulation resistance: 10 MΩ min.
- Contact resistance: 2 Ohm max.
- Supported power throughput: 15.0 W

Operating Environment

- Operation temperature: 0 - 45°C (32 - 113°F)
- Operating humidity (non-condensing): 10 - 85%
- Storage temperature: -10 - 70°C (14 - 158°F)
- Storage humidity (non-condensing): 5 - 90%

Package Contents

- Coiled USB-A to USB-C Charging Cable

This product is part of a group; the complete list of variations follows:

- #356213 - USB-C Male to USB-C Male
- #356220 - USB-A Male to USB-C Male
- #356237 - USB-A Male to Micro-USB Male
- #356244 - USB-C Male to Micro-USB Male

