



# USB-C to HDMI (4K@30Hz) 3-in-1 Docking Converter with Power Delivery

USB 3.2 Type-C Male to HDMI (4K@30Hz), USB-A (5 Gbps) and USB-C PD (100 W) Females, Multiport Converter with Pass-through Charging Port, Aluminum, Space Gray

Part No.: 130707

EAN-13: 0766623130707 | UPC: 766623130707

# USB-C to HDMI Adapter to connect a laptop, MacBook®, smartphone or tablet to an HDMI display - plus a USB-A peripheral and Power Delivery charging port

The Manhattan USB-C 3-in-1 HDMI Docking Converter with Power Delivery establishes a fast, simple and convenient link between a newer USB Type-C equipped media source (a laptop, PC, MacBook®, Chromebook™, computer, tablet, etc.) and existing HDMI display (monitor, TV or projector) for 4K at 30 Hz images in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.2 Gen 1 (formerly USB 3.0) peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB-A port. This multiport Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your USB-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

# **Up to 100 W charging power with USB-C Power Delivery (PD)**

The included USB-C PD port lets you charge your notebook with power up to 100 W while simultaneously charging your other mobile devices, such as smartphones or tablets, through the USB-A port. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest rate.

# manhattan-products.com



# Take your phone to the big screen

If you have a smartphone or tablet that supports video output over USB-C DP Alt Mode, you can enjoy your apps and media even more. Watch a video on your monitor or flip through the slides of your presentation on a projector - all from your phone.

# A multiport adapter that's made to go where you go

The very compact aluminum housing makes this USB-C to HDMI Converter the perfect travel companion. It's small enough to fit in an outer notebook bag pocket, so you can create a mini-workstation for your laptop where ever you're going.

#### **Features:**

- Easily connects a USB-C device to an HDMI display and USB-A peripheral while also charging both USB devices
- Resolutions up to Ultra-High-Definition (UHD) 4K@30Hz (3840×2160)
- One USB 3.2 Gen 1 Type-A port (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps and charging up to 5 W (5 V / 1 A)
- USB-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- Supports USB Power Delivery (PD) function up to 100 W; requires an external PD charger - available from Manhattan
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple® MacBook®, Chromebook™, Pixel™ and more
- Sturdy, sleek aluminum housing, great for both desktop and travel
- Built-in, sturdy 11 cm (4 in.) cable
- Fully HDCP 1.4 compliant, backward compatible
- Lets your smartphone work like a desktop PC while also charging it (desktop setup requires devices with Android 9 or above that offer video output over USB-C)
- Plug-and-play installation; Windows®, macOS®, Linux®, Chrome OS™, iPadOS® and Android™ compatible
- Three-year warranty

## **Specifications:**

Standards and Certifications

- DP 1.2 Alt Mode over USB-C
- USB 3.2 Gen 1
- HDMI 1.4



# manhattan-products.com

- HDCP 1.4
- CE
- FCC
- RoHS
- REACH
- UKCA

#### General

- USB-A port data transfer speed: 5 Gbps
- Bus powered operation (except charging functions)
- USB-C PD charging port: 100.0 W (20.0 V at 5.0 A) max.
- USB-A charging: 5.0 W (5.0 V at 1.0 A) max.

#### Connections

- One USB-C 24-pin, male
- One USB-C 24-pin, female
- One USB-A 4-pin, female
- One HDMI 19-pin, female

### Physical

- Dimensions (L x W x H): 71 x 29 x 12 mm (2.8 x 1.14 x 0.47 in.)
- Net weight: 31 g (1.09 oz.)
- Gross weight: 55 g (1.94 oz.)
- Cable length: 11 cm (4 in.)
- Cable diameter: 34 AWG
- Aluminum housing

#### Operating Environment

- Operation temperature: 0 45°C (32 113°F)
- Storage temperature: -10 70°C (14 158°F)
- Humidity (noncondensing): 5 90% RH

### System Requirements

• Windows 7/8.1/10/11, Linux, Chrome OS, macOS, iPadOS or Android

#### Package Contents

- USB-C to HDMI 3-in-1 Docking Converter with Power Delivery
- Instructions





# manhattan-products.com









