



Introduction

The Atlona **AT-OME-TX21-WP-E** is a 2×1 switcher and HDBaseT transmitter with HDMI and USB-C inputs. It is designed for commercial installations in Europe. The OME-TX21-WP-E includes interchangeable EU and UK faceplates and brackets. The USB-C input is ideal for AV interfacing with Mac®, Chromebook™, and Windows® PCs, as well as smartphones and tablets. Video signals up to 4K/UHD @ 60 Hz with 4:2:0 chroma subsampling, plus embedded audio and control can be transmitted up to 330 feet (100 meters). The OME-TX21-WP-E is HDCP 2.2 compliant. It is designed for use with Omega™ Series receivers and switchers, select HDVS Series receivers, the AT-UHD-EX-100CE-RX-PSE receiver, and other Atlona switchers with HDBaseT inputs. This transmitter can serve as an integral component of a fully automated AV system, with the convenience of automatic input selection and display control. It is remotely powered by Atlona HDBaseT-equipped devices through Power over Ethernet (PoE).

Applications

- **Complete system integration**
The OME-TX21-WP-E and a compatible HDBaseT receiver provide a compact, yet comprehensive and cost-effective integration solution.
- **Larger system applications**
The OME-TX21-WP-E is ideal for extending AV connectivity from a central equipment rack to lecterns as well as remote wall and floor box locations, where presenters can easily access the system.

Key Features

Two-gang enclosure for EU and UK wallplate openings – interchangeable EU and UK trim kits

- Allows inconspicuous installation on a wall, in furniture, or in a floor box.
- Meets end user requirements for conveniently accessible yet discreet AV connectivity.

2x1 HDBaseT switcher with HDMI and USB-C⁽¹⁾ inputs

- Immediate compatibility with laptops and tablets with USB-C ports supporting AV.
- No need to provide USB-C to HDMI adapters.

HDBaseT transmitter for AV, power, and control up to 330 feet (100 meters)

- Uses easy-to-integrate category cable for low-cost, reliable system installation.
- Can easily be mixed and matched with Atlona power sourcing (PSE) receivers and switchers depending on system design requirements.

HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

Remotely powered via PoE (Power over Ethernet)

- Power for transmitter is supplied by Atlona receiver or switcher over HDBaseT.
- Saves time and integration costs.

Automatic input selection and automatic display control

- Automatically changes display power state, and switches between inputs based on device connection or disconnection (hot-plug detection) from the switcher. Also can be configured to power off display after a period of inactivity.
- Enables effortless, automated system operation without the need for an external control system.

TCP/IP and RS-232 control of switcher

- Flexible control options for compatibility with Velocity™ and third-party control systems. TCP/IP control available through a compatible receiver or HDBaseT-equipped switcher.
- Reduces integration time and costs.

Specifications

Video	
Signal	Input - HDMI / USB-C Output - HDBaseT
Copy Protection	HDCP 2.2
Pixel Clock	300 MHz
UHD/HD/SD	4096x2160 @ 60 ⁽¹⁾ /50 ⁽¹⁾ /30/25/24 Hz 1280x720p @ 60/59.94/50 Hz 3840x2160 @ 60 ⁽¹⁾ /50 ⁽¹⁾ /30/25/24 Hz 720x576p 2048x1080p 720x576i 1920x1080p @ 60/59.94/50/30/29.97/25 640x480p /24/23.98 Hz 640x480i 1920x1080i @ 60/59.94/50 Hz
VESA All resolutions are 60Hz	2560x2048 1366x768 2560x1600 1360x768 2048x1536 1280x1024 1920x1200 1280x800 1680x1050 1280x768 1600x1200 1152x768 1600x900 1024x768 1440x900 800x600 1400x1050 640x480
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit

Audio			
HDMI / HDBaseT Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD	DTS® Digital Surround™ DTS-HD Master Audio™
Bit Depth	Up to 24 bits		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	230	70	330	100
CAT6/6a/7	230	70	330	100

RS-232	
Port	1 x 3-pin captive screw
Use	Pass-through from control system to sink device
Baud Rates	2400, 4800, 9600, 19200, 38400, 57600, 115200
Data flow	Bidirectional

Indicators and Buttons	
Indicators: HDMI, PWR, AUTO, USB-C, LINK	5 x LED, green
Buttons: INPUT RESET IP TEST	1 - Push button, momentary, tact-type 1 - Push button, momentary, tact-type 1 - Push button, momentary, tact-type 1 - Push button, momentary, tact-type

Connectors	
HDMI	1 x Type A, 19-pin female, locking
USB-C ⁽²⁾	1 x USB Type-C, 24-pin, female
RS-232	1 x 3-pin captive screw
HDBaseT OUT	1 x RJ45

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +104	0 to +40
Storage Temperature	-4 to +140	-20 to +60
Operating Humidity (RH)	20% to 90%, non-condensing	

Power	
Consumption	10.2 W
BTU/h	34.8

Dimensions (H x W x D)	Inches	Millimeters
EU version	5.98 x 3.19 x 1.77	152 x 81 x 45
UK version	5.79 x 3.44 x 1.77	147 x 87.5 x 45

Weight	Pounds	Kilograms
Device	0.50	0.23

Certification	
Device	CE, RoHS, FCC

Compliance	
NDAA-899	Yes

Warranty	
Device	To view the product warranty, use the following link: https://atlonacom/warranty

Footnotes

(1) HDMI and USB-C inputs support up to 4K/UHD @ 60 Hz YUV 4:4:4 8-bit. HDBaseT output supports 4K/UHD @ 60 Hz YUV 4:2:0 only. An input of 4K/UHD @ 60 Hz YUV 4:4:4 will be converted to output 4K/UHD @ 60 Hz YUV 4:2:0.

(2) The USB-C port does not support data or charging of external devices.

Copyright, Trademark, and Registration

© 2024 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).