TY-SB01QS

This terminal board is supported only when the main software version of the display is 2.30 or later and the sub software version of the display is 02.20 or later. Please contact your sales representative with regard to details.

Panasonic
CONNECT

TY-SB01QS

Terminals | SDI 1 IN	BNC x 1 : 0.8Vp-p (75Ω)
Terminals | SDI 2 IN	BNC x 1 : 0.8Vp-p (75Ω)
Terminals | SDI 3 IN	BNC x 1 : 0.8Vp-p (75Ω)
Terminals | SDI 4 IN	BNC x 1 : 0.8Vp-p (75Ω)
	3840/60p,50p,30p,25p,24p 4096/60p,50p,30p,25p,24p
	Intel® SDM slot specification
	BNC x 1 : Active through
Audio	12G-SDI: SMPTE ST 299（SDI 1 IN Only）3G-SDI: SMPTE ST 299（SDI 1 IN Only）HD-SDI: SMPTE ST 299（SDI 1 IN Only）
Video	12G-SDI: SMPTE ST 2082-1 / 2082-10（SDI 1 IN Only）3G-SDI: SMPTE ST 424 / 425 HD-SDI: SMPTE ST 292 Quad Link 3G-SDI： SMPTE ST 424 / 425-5 Quad Link HD-SDI
	1080/60p, 50p, 30p, 25p, 24p, 60i, 50i 2048/60p,50p,30p,25p,24p
	1080/30p, 25p, 24p, 60i, 50i
	48KHz, 20/24bit, 16CH, Synchronized video
	48KHz, 20/24bit, 16CH, Synchronized video
	48KHz, 20/24bit, 8CH, Synchronized video
Weight	0.7 lbs. (300 g)
Dimensions (W x H x D)	W 7.68" x H 0.99" x D 4.90" (195 x 25 x 125 mm)
Note	This product is a 12G-SDI terminal board that can be used by attaching it to our display. * This product does not work by itself. * This product will not work if it is installed on a product other than the corresponding model. * Please consult with a professional engineer or dealer to install or remove this product from the display.