



Features:

- 24/7 Operation
- IPS, that prevents system errors when power loss (Optional)
- ECC, preventing corrupt data on the system
- Very small slim design, with only 26 mm depth
- JAHC for scheduling ON/OFF during a week
- System bracket for VESA (Optional)
- Dual digital signal output



CPU	Intel® Celeron N5100 10 nm, TDP 6W, 4 cores, 4 MB L3 Cache
Frequency	1.10 Ghz (up to 2.80 Ghz)
BIOS	AMI Source code
Chipset	SOC
Memory	4 GB DDR4
GPU	Intel® UHD Graphics
Displayport	1 x DP (Max.4096x2160 @60Hz)
HDMI	1 x HDMI (Max.4096x2160@60Hz)
Network	2 x Realtek 8111H Gigabit Ethernet (RJ45)
USB	2 x USB 3.2, 4 x USB 2.0
Serial Port	1 x RS232
Audio	1 x AUDIO-OUT & SPDIF, 1 x MIC-IN
Storage	1 x 2,5" SATA 1 x Full-size mSATA

Mini-PCle	1 x Full-size Mini-PCle for WiFi/BT/3G/4G
JAHC	WatchDog Timer Auto Power On RTC Remote Control
Operating System	Windows 7, 8.1, 10, Linux
Power Req.	DC-IN, 19V/2.37A
Fanless	Yes
Construction	Metal
Operation temp.	0°C ~ 40°C (32°F ~ 104°F)
Mounting (Optional)	ALPHA VESA Bracket ALPHA Wallmount with player bracket
Relative Humidity	95% @ 40°C (non-condensing)
Color	Black
Certification	CE, FCC Class B
Dimensions	189.6mm x 148.3mm x 26mm