

Connect the dock to your host computer, using the included 3.3ft (1m) USB-C cable. The docking station supports all major operating systems, including Windows, macOS, ChromeOS, and Ubuntu. This dock was designed for seamless integration with any compatible USB-C equipped device within your organization, including Lenovo X1/Thinkpad P Series, Dell Latitudes/Precision/XPS 15, HP Envy, Surface Laptop 3, and M1 Pro/Max/M2 MacBooks. The dock features a side-facing K-Slot for added security in shared workspaces (e.g., BYOD hoteling/hot-desking).

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

Advanced Windows Layout Utility: Setup and save custom windows layouts.

Mac Address Pass-Through Utility: Improve network security.


USB Event Monitoring Utility: Track and log connected USB devices.

Wi-Fi Auto Switch Utility: Enable users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit:
www.StarTech.com/Connectivity-Tools

This product is backed for 3-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility



Applications

- Use in laptop hot-desk workstations for hoteling
- Charge your tablets and smartphones from the B.C 1.2 USB ports

Features

- HIGH-PERFORMANCE TRIPLE 4K VIDEO: USB C Multi Monitor Docking Station features flexible video outputs that enable you to connect two 4K 60Hz HDMI 2.0 and/or DisplayPort 1.2 (DP++) monitors via DisplayLink and a 3rd 4K 30Hz HDMI monitor via DP 1.2 Alt Mode

- **UNIVERSAL COMPATIBILITY:** Compatible with Windows, macOS, ChromeOS & Ubuntu, enabling extended triple displays on USB-C & Thunderbolt 3 and 4 laptops including Apple M1/M2 MacBooks which are not natively capable of driving more than one external display
- **FULL FEATURE DOCK:** 5-Port USB Hub with 3x USB-A (2x 5Gbps, 1x 10Gbps w/BC 1.2 charging) and 2x USB-C (1x 10Gbps w/BC 1.2, 1x 5Gbps) - 100W USB PD - 3.5mm Headset/Audio port and Gigabit Ethernet (WoL) - K Slot - OCP protects devices from power surges
- **100W POWER DELIVERY 3.0:** Power and charge USB-C and Thunderbolt 3/4 laptops and ultrabooks including Lenovo X1/Thinkpad P Series, Dell Latitudes/Precision, XPS 15, HP Envy, Surface Laptop 3 and MacBook - Incl. 3.3ft/1m USB-IF Certified USB-C host cable
- **CONNECTIVITY TOOLS:** Optimize the performance and security of this universal docking station, using the included MAC Address Changer, USB Event Monitoring, Windows Layout and Wi-Fi Auto Switch utilities (available for download)

Hardware

Warranty	3 Years
4K Support	Yes
Fast-Charge Port(s)	Yes
Displays Supported	3
Audio	Yes
Interface	USB 3.2 Gen 2 10Gbps
Bus Type	USB 3.2 Gen 2
Compatible Lock Slot	Kensington Standard Slot (K-Slot)
Industry Standards	HDMI 2.0
	DisplayPort 1.4
	USB 3.2 Gen 2 (10Gbps)
	USB 3.2 Gen 1 (5Gbps)
	1000Base-T, 100Base-TX, 10Base-T (IEEE802.3ab compliant)
	Wake-on-LAN (WoL)
Chipset ID	DisplayLink - DL-6950-N
	VIA - VL817C0
	Parade - PS176C0

Performance

Maximum Data Transfer Rate	10Gbps
Maximum Digital Resolutions	2x HDMI and/or DisplayPort: 4K (4096 x 2160) 60Hz 1x HDMI (via DP Alt Mode): 4K (4096 x 2160) 30Hz
Type and Rate	USB 3.2 Gen 2 - 10 Gbit/s
Supported Charging Outputs	BC 1.2 (1.5A)
Compatible Networks	10/100/1000 Mbps
MTBF	44,877 Hours

Connector(s)

External Ports	3 - HDMI (19 pin) 2 - DisplayPort (20 pin) 1 - USB 3.2 Type-A (9 Pin, Gen 2, 10Gbps, 7.5W Power) 1 - USB 3.2 Gen 2 USB Type-C (Fast-Charge, 24 Pin, 10 Gbps) 1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps) 2 - USB 3.2 Type-A (9 pin, Gen 1, 5Gbps) 1 - 3.5 mm Mini-Jack (4 Position) 1 - RJ-45
Host Connectors	1 - USB 3.2 Type-C (24 pin, Gen 2, 10Gbps)

Software

OS Compatibility	Windows 7, 8, 8.1, 10, 11 >macOS 10.11 to 10.12, 10.14 to 10.15, 11.0, 12.0, 13.0 >Android >Linux 3.5.x and up - <i>LTS Versions only</i> >ChromeOS
------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------

Special Notes / Requirements

System and Cable Requirements	A host device with an available USB-C port (to ensure full adapter functionality, the host device's USB-C port must support USB Power Delivery 2.0 and DP alt mode).
Note	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure your host device's USB-C port

supports USB Power Delivery and DP alt mode.

A 4K-capable display is required to achieve 4096 x 2160p/3840 x 2160p resolution.

A 4K-capable computer is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K) on the DP Alt-Mode HDMI port.

USB 3.2 Gen 1 (5Gbps) is also known as USB 3.1 Gen 1 (5Gbps) and USB 3.0 (5Gbps).

Indicators

LED Indicators	1 - Power LED (white)
----------------	-----------------------

Power

Power Source	AC Adapter Included
Power Delivery	100W
Input Voltage	100 - 240 AC
Input Current	2.5 A
Output Voltage	24 DC
Output Current	5.41 A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption (In Watts)	15W

Environmental

Operating Temperature	0C to 70C (32F to 158F)
Storage Temperature	-10C to 55C (14F to 131F)
Humidity	0~85% RH (Non-condensing)

Physical Characteristics

Color	Space Gray
Material	Plastic
Product Length	7.5 in [19.0 cm]

Product Width	3.3 in [8.5 cm]
Product Height	1.2 in [3.0 cm]
Weight of Product	12.4 oz [350.0 g]

Packaging Information

Package Length	9.8 in [25.0 cm]
Package Width	8.1 in [20.5 cm]
Package Height	2.0 in [5.0 cm]
Shipping (Package) Weight	2.4 lb [1.1 kg]

What's in the Box

Included in Package	1 - USB-C Docking Station
	1 - 3 ft [1 m] USB-C Host Cable
	1 - Power Adapter (UK)
	1 - Quick-Start Guide

****Product appearance and specifications are subject to change without notice.***