

DIGITUS Network cabinet Varioflex-N Series - 800x1000 mm (WxD)

DN-43001
EAN 4016032486923



42U network cabinet, Varioflex-N 2022,6 x 800 x 1000 mm, grey

The network cabinets from the Varioflex-N series were designed and produced for optimum cabling of network components. Clever optimizations offer market-compliant stability with maximum flexibility. The front door, consisting of a full metal frame with 4 mm thick tempered glass, and the double-wing steel rear door are both equipped with a swing handle including a profile half-cylinder lock (DIN 18 252 (EN 1303)). Both side walls can be locked and removed. Integrated inside the cabinet are four cranked, galvanized 19" profiles, which are connected to the base frame of the cabinet at several points using depth bars. The depth is adjustable, and they have markings for the respective rack unit, which can be read in both directions. A modular base chassis that can be opened by means of screwed blank panels offers plenty of space for cables of all kinds. Furthermore, there are two cable inlets with brushes at the top and bottom of the cabinet. The versatile features of the network cabinet are perfectly completed by generous vertical cable channels with plastic cable routing rings and trim panel, built into the front.

The Varioflex-N series has been designed and manufactured for the high demands of IT infrastructure. It offers maximum stability and flexibility in a wide range of usage scenarios.

- Protection type IP20
- Front door consists of full metal frame with 4 mm thick tempered glass
- Steel rear door, double folding
- Swing handle with profile half-cylinder lock incl. key on front and rear doors
- 120° door opening angle
- Side sections can be locked and removed
- incl. 4 levelling feet, which are already fitted under the cabinet
- 483 mm (19") profile rails mounted on the front and rear of the cabinet, galvanized

- 483 mm (19") profile rails are connected to the main frame by depth bars at 4 points each on the left and right
- 483 mm (19") profile rails are adjustable in depth and have markings for the rack units
- 483 mm (19") profile rails with high load capacity of up to 1200 kg
- Installation depth for components min. - max.: 290-770 mm
- Roof is set up to accommodate a fan unit and an attached, removable cover
- Modular, openable base chassis with removable blank panels (400 mm wide)
- Generously dimensioned vertical cable channels with cable routing and trim panel built into the front panel
- Cable inlets in base and roof with brush strip left and right (70 x 316 mm)
- Numerous plug-in earthing points for earthing cables (Faston connector)
- Numerous plug-in earthing points for earthing cables (Faston connector)
- Delivered fully assembled
- Product dimensions (H x W x D): 2022.6 x 800 x 1000 mm
- IP protection class: IP20
- Color: light grey, RAL 7035
- Depth: 1000 mm
- Front door: Glass door, single opening
- Units: 42
- Load capacity: 1200 kg
- Mounted: yes
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Cabinet type: Network cabinet
- Width: 800 mm

Package contents

- Earthing cable set
- Installation set (screws, captive nuts, washers)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.00	105.00	85.00	207.26	1,849,800.00
Packaging Unit Inside	1	0.00	105.00	85.00	207.26	1,849,800.00
Packaging Unit Single	1	0.00	105.00	85.00	207.26	1,849,800.00
Net single without Packaging	1	0.00	100.00	80.00	202.26	1,618,080.00

More images:

