

Combi Drill G-Battery

HP488DAEX1

18V • 42 Nm • 0 – 1 400 min⁻¹

G-Series cordless hammer driver drill for demanding use

All metal gear construction ensures high transmission durability. Compact and lightweight design for easy handling and high maneuverability. Electric brake for maximum productivity and increased operator safety. Two 2,0 Ah batteries and a charger.



18V

Technical specifications

G-series	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 400 / 1400 min ⁻¹
Max. fastening torque Hard/Soft	42 / 24 Nm
Torque setting	16
Max Torque	47 Nm
Impacts per Minute (IPM)	0 - 6000 / 21000 min ⁻¹
Drilling Capacity Wood (Auger Bit)	36 mm
Drilling Capacity Wood (Self-feed bit)	35 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drilling Capacity Flat bit	36 mm
Drilling Capacity Hole Saw	51 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm

User benefits

- The rubber coating on the handle ensures a firm working grip
- Compact and lightweight design
- Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque
- Low noise level for pleasant work.

EAN 0088381734912

Link to product - www.makita.com



Related products

■ Standard AC

687010-0

Band, 5704R

■ Standard MA

BL1820G (2x)
G-Series Battery



DC18WA
Battery Charger G-Series



■ Other

[User manual](#)

[Parts drawing](#)