

FEATURES

- 8-Channel Hybrid DVR
- Compatible with AHD, TVI, CVI, and Analog Cameras
- 8Mbps IP Channel Throughput
- Bolide QuickConnect Mobile App
- Bolide VMS Software for PC and Mac

DVR SPECIFICATIONS

Recording Bandwidth

Inputs	8Mbps ~ 40Mbps IP Bandwidth Max is 8Mbps, Decrease One Analog Channel Can Increase 4Mbps (Default Decoding Performance 1080P 60FPS)
Output	56Mbps
Analog Video Input	8 Channels BNC

Live

IP Video Input	2 Channels
Composite Video In	Up to 10 Channels (Analog+ IP)

Recording and Playback

Compression	Audio: G.711a Video : H.264/H.265
Display Resolution	1080N/720P/960H:30fps IP:1080P/720P Single IP Channel Preview up to 2MP 30FPS Multi-Channel, Preview Only Sub-Stream
Speed	<u>Main Stream:</u> 1080N (960*1080):30FP 720P: 30FPS / Channel IP: PAL:25FPS / Channel NTSC: 30FPS / Channel <u>Sub-Stream:</u> PAL : 704*576: 10FPS / Channel NTSC : 704*480: 10FPS / Channel



Playback	60FPS (Max 4CH Playback)
Playback Function	Fast Forward / Backward (2x, 4x, 8x, 16x) Slow Forward (1/2x, 1/4x, 1/8x, 1/16x) Yes, Audio Over Coax
Audio	No
Audio In/Out	No
Video Output	1x HDMI
Ethernet	1x RJ45 10/100Base-T
USB	2x USB 2.0
HDD	1x SATA Up to 12TB

General

Dimensions	9.05in (L) x 8.46in (W) x 1.85in (H)
Voltage / Current	12VDC 2A
Power Consumption (Excluding HDD)	4W
Operating Temp.	32°F ~ 104°F
Op. Humidity	Less than 90%RH

Remote Access

Bolide QuickConnect App For iOS and Android

Bolide VMS For PC and Mac (Free Download)