

# Product datasheet

Specifications



## Rack PDU, Basic, 1U, 14.4kW, 208V, (6) C19



AP7516

EAN Code: 0731304232674

### Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.4 m
Provided equipment	Installation guide Rack mounting brackets

### Complementary

Input Voltage	208 V 3 phases
Height	44 mm
Width	437 mm
Output Voltage	200 V 208 V
Depth	254 mm
Product weight	7.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
[In] rated current	40 A
Input current limits	50 A
Load capacity	14400 VA
Network frequency	50/60 Hz
Number of input connectors	1 CS8365
Outlet type and quantity	6 IEC 60320 C19

### Environment

Product certifications	cUL listed METI Denan UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	-5...45 °C

---

Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15240 m

---

## Packing Units

---

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	50.2 cm
Package 1 Length	55.9 cm
Package 1 Weight	10.1 kg

---

## Logistical informations

---

Country of origin	IN
-------------------	----

---

## Contractual warranty

---

Warranty (in months)	24
----------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	23 328 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	23 290 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>
Halogen-free status	Product contains halogen above thresholds

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	45
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

---





