

MPN: 0070-24143

43" 24/7 4K UHD surveillance monitor.

Industrial-grade LED screen. Metal chassis design

PRODUCT CHARACTERISTICS

- 4K HD solution
- Industrial-grade LED screen
- Designed for CCTV
- High brightness, high contrast, high definition
- Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178° wide viewing angle
- High fidelity digital processing, brilliant and vivid video
- 24/7 working status, working continuously for 5 years
- Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation

VESA size: 200x200

- 4K HD Solution
- 7/24 working Status Security monitor
- High brightness, High contrast, High definition
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178 ° wide viewing angle
- Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation
- Humanize Menu
- Convenient Controller
- HDMI cable included
- 5 Year Warranty



Specifications

Design	Detachable stand	Yes
	Front bezel colour	Black
	Market positioning	Industrial
	Product colour	Black
Display	3D	Yes
	Aspect ratio	16:9
	Backlight type	LED
	Contrast ratio (typical)	1200:1
	Display brightness	350 cd/m ²
	Display brightness (typical)	350 cd/m ²
	Display diagonal	43 "
	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED

Display	HD type	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.2451(H)×0.2451(V) mm
	Response time	5 ms
	Viewable size, horizontal	94.1 cm
	Viewable size, vertical	52.9 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	On Screen Display (OSD) languages	English
	Panel mounting interface	200 x 200 mm
	VESA mounting	Yes
Operational conditions	Operating temperature (T-T)	-30 - +85 °C
Other features	Accessories included	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	941.184mm(W)×529.146mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 200 x 200
	Contrast ratio	1200:1
	Dimensions (WxDxH)	972 x 88 x 576 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 200 x 200 mm
	Noise filter	Yes
	Number of colours	1.073 billion colours
	Package dimensions (WxDxH)	1085 x 232 x 680 mm
	Picture enhancement	DNle digital image processing
	Power consumption	100 W
	Speakers	2x3W
	Weight	19800 g
Packaging content	Power adapter included	Yes
	Quick start guide	Yes
	Screws included	Yes
	Stand included	Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	DisplayPorts quantity	1
	HDMI ports quantity	3
	HDMI version	2.0
Power	AC input frequency	50/60 Hz
	AC input voltage	100-240 V

Power	Power consumption (average)	100 W
	Power supply type	Industrial
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
8	0070-24108-M
10.1	0070-24110-M-L
19	0070-24119-M
22	0070-24222-AC-M
32	0070-24232-M
43	0070-24143
49	0070-24149
55	0070-24155
65	0070-24165
75	0070-24175
86	0070-24186
98	0070-24198

Other images

