

MPN: 0070-24149

49" 24/7 4K UHD surveillance monitor. Industrial-grade LED screen. Metal chassis design

Ernitec 49" Monitor: Exceptional 4K UHD Performance

Introducing the Ernitec 49" Monitor, a powerful display solution tailored for CCTV applications. With its 4K UHD resolution, this industrial-grade LED screen delivers outstanding image quality, ensuring high brightness, contrast, and clarity.

Key Features:

Stunning Visuals: Experience high definition with advanced 3D digital filtering and noise reduction technology for crystal-clear images.

Rapid Response: Enjoy fast picture response times and a 178° wide viewing angle, providing consistent quality from any position.

Reliable Operation: Built for 24/7 use, this monitor is designed to operate continuously for up to 5 years, making it a dependable choice for security monitoring.

Durable Design: The robust metal chassis is anti-static, anti-magnetic, and resistant to interference, ensuring safe operation without radiation.

User-Friendly Interface: Navigate effortlessly with a convenient controller and intuitive menu system.

Flexible Mounting: Compatible with VESA 400x200, allowing for easy installation in various environments.

The Ernitec 49" Monitor is your ideal partner for high-performance surveillance, combining durability with exceptional visual quality.

Upgrade your security setup today!

- 4K HD Solution
- 7/24 working Status Security monitor
- High brightness, High contrast, High definition
- Adapt newest 3D digital filtering and 3D digital noise reduction technology
- Picture fast response
- 178 ° wide viewing angle
- Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation
- Humanize Menu
- Convenient Controller
- HDMI cable included
- 5 Year Warranty



Specifications

Design	Detachable stand	Yes
--------	------------------	-----

Design	Front bezel colour	Black
	Market positioning	Enterprise
	Product colour	Black
Display	3D	Yes
	Aspect ratio	16:9
	Backlight type	LED
	Contrast ratio (typical)	5000:1
	Display brightness	500 cd/m ²
	Display brightness (typical)	350 cd/m ²
	Display diagonal	49 "
	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED
	HD type	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.315(H)×0.315(V) mm
	Response time	5 ms
	Viewable size, horizontal	107.6 cm
	Viewable size, vertical	60.6 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	On Screen Display (OSD) languages	English
	Panel mounting interface	400 x 200 mm
	VESA mounting	Yes
Operational conditions	Operating temperature (T-T)	-30 - +85 °C
Other features	Accessories included	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	1095.84mm(W)×616.41mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 400 x 200
	Contrast ratio	4000:1
	Dimensions (WxDxH)	1103 x 76 x 649 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 400 x 200 mm
	Noise filter	Yes
	Number of colours	1.073 billion colours
	Package dimensions (WxDxH)	1247 x 232 x 765 mm
	Picture enhancement	DNle digital image processing
	Power consumption	110 W
	Speakers	2x3W (Stereo)

Other features	Weight	24300 g
Packaging content	Power adapter included	Yes
	Quick start guide	Yes
	Screws included	Yes
	Stand included	Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	DisplayPorts quantity	1
	HDMI ports quantity	3
	HDMI version	2.0
Power	AC input frequency	50/60 Hz
	AC input voltage	100-240 V
	Power consumption (average)	120 W
	Power supply type	Industrial
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
8	0070-24108-M
10.1	0070-24110-M-L
19	0070-24119-M
22	0070-24222-AC-M
32	0070-24232-M
43	0070-24143
49	0070-24149
55	0070-24155
65	0070-24165
75	0070-24175
86	0070-24186
98	0070-24198

Other images

