

Product Safety Data Sheet

SDS #: 23-00742

2023-08-30

Revision 2

Xerox® VersaLink C625

Product Identifier
Speed (PPM)
Mono / Color

Multifunction Device (MFD) 7530-6e8
 52
 Colour

ELECTRICAL INPUT INFORMATION

	110V-127V	220V-240V
Voltage (Volts)		
Rated Current (Amperes):	10.0	5.0
Frequency (Hertz)	50/60	50/60
Phase Connection	single	single

POWER AND HEAT

TEC Value (kWh/wk) 0.71 0.76

	Power (Watts)	Heat Output (BTU/Hr)	Power (Watts)	Heat Output (BTU/Hr)
Active ¹	716.1	2443.3	665.8	2271.7
Ready ¹	46.4	158.3	49.4	168.6
Sleep ¹	1.46	5.0	1.43	4.9
Standby ¹ (Off/FEMP) ²	0.1	0.34	0.1	0.34

¹ Power states defined per ENERGY STAR Program requirements for Imaging Equipment.

² FEMP - Federal Energy Management Program

Note: The electrical power information provided should not be used to define the electrical support required for this product. Consult your Xerox representative if you require detailed information.

OPERATING ENVIRONMENT

Relative Humidity % 10-85
 Ambient Temperature 50-90 °F / 10-32 °C

PRODUCT SIZE

Depth	20.9 in.	53.3 cm
Width	18.9 in.	47.9 cm
Height	24.4 in.	62.1 cm
Weight	86.0 lbs	39.0 kg

SPACE REQUIREMENTS

Refer to Users Guide

For additional information regarding different configurations please contact your local sales representative.

LIGHT SOURCE:

Class 1 Laser Product

Chemical Emission Test Methodology DE-UZ-219

The machine was tested under the conditions as specified in the standard inside a room of 4.0 m³ with 1 air change per hour.

PARAMETER

Total Volatile Organic Compounds (TVOC)
 Dust
 Ozone
 Styrene
 Benzene

Emission Rate

3.647 mg/h
 < Limit of detection
 < Limit of detection
 0.067 mg/h
 < Limit of detection



Product Safety Data Sheet

ACOUSTICAL NOISE

Tested in accordance to ISO 7779 and declared per ISO 9296

	Sound Power Level LwAd (B)	Sound Pressure Level Lpam (dBA)
Standby	3.1	14.0
Run - continuous	7.0	55.0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Emergencies US only: 1-585-422-2177
Inquiries US only: 1-800-828-6571
Contact US only: usa.xerox.EHS@xerox.com
Contact Non US only: ehs-europe@xerox.com