


Wiremold Omnibox® Series Triple Gang Cast Iron Floor Box

Part No. 880CS3-1



The 880CS3-1 three gang Omnibox® Floor Box provides an excellent activation solution for applications where multiple services are required in open space areas. The 880CS3-1 floor box is offered in a stamped steel construction, designed to be installed in above grade concrete floor applications and to meet a wide range of market requirements.

This floor box series has many applications, some of which are schools, financial institutions, and commercial office buildings.

Features & Benefits

TopGuard protection. All cover assemblies for the Omnibox Floor Box Series have TopGuard protection. An integral design which keeps out water, dirt, and debris from the power and communication compartments.

Fully adjustable box. Before and after concrete pour adjustability. Lower installed cost.

Watertight cast-iron construction. Meets requirements for on grade or below grade application Three-gang configurations, maximum flexibility. Can remove divider for greater capacity. Supports multiservice applications.

Boxes and covers have been listed by Underwriters Laboratories Inc. to their standard UL514A, 514C, 514D, and Canadian standard C22.2

Flush activation assemblies for carpet and tile. Aesthetically pleasing assemblies are steel

Datacom connectivity options. Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications interchangeable for both cast-iron and stamped at the point-of-use. A wide selection of data and bezel options available for use with Ortronics TracJack and Series II devices.

Specifications

General Info Product Line Wiremold Color Silver **UPC** Number 786564515890 Country Of Origin China Assembled Number of Knockouts Construction 1 cULus Listed Metallic Outlet Boxes: File E2961 **Application Sector** Standard Commercial Guide QCIT. Meets Article 314.27(C) of NEC.

Туре	Floor Box		
Dimensions			
Product Width US	5.38 in	Product Weight US	13.4 lb
Product Volume US	265.31 cu in	Product Depth US	14.63 in
Product Height US	3.38 in	Cubic Capacity	160 in3
Listing Agencies / 3rd Pa	rty Agencies		
cULus ListingNumber	E2961	cULus Listed	Yes
Additional Information			
RoHS Conformant	Yes	Product Environmental Profile	Yes
Technical Information			
Cable Entry	Conduit Threads	Number of Outlets	0