

Wiremold 2400D Device Bracket Fitting

Part No. 2450-FW



For use with 2400D-2N. Allows both power and low voltage at a single point-of-use. Accepts 5507 Series Faceplates, Ortronics TracJack and Series II Modules (requires S2-EPL Plate), Pass and Seymour Activate Series Inserts (requires CM-EPLA Plate), and Wiremold Open System Communication Modules (requires CM-EPLA Plate).

Features & Benefits

For use with 2400D-2N. Allows both power and low voltage at a single point-of-use. Accepts 5507 Series Faceplates, Ortronics TracJack and Series II Modules (requires S2-EPL Plate), Pass and Seymour Activate Series Inserts (requires CM-EPLA Plate), and Wiremold Open System Communication Modules (requires CM-EPLA Plate).

Specifications

General Info			
Product Line	Wiremold	UPC Number	786776138313
Country Of Origin	United States	Application Sector	Residential/Commercial
Standard	cULus Listed Raceway: FileE4376 Guide RJBT. Fittings: File E41751 Guide RJPR. Base & Blank Cover: Meets Article 386 of NEC. Meets Section 12-600 of CEC.	Туре	Raceway
Dimensions			
Product Width US	4.625 in	Product Height US	0.375 in
Product Length US	4.625 in		
Listing Agencies / 3rd Party Agencies			
cULus ListingNumber	E41751	cULus Listed	Yes
Product Length US Listing Agencies / 3r	4.625 in ad Party Agencies		

Buy American Act Compliance

NAFTA	Yes			
Additional Information				
RoHS Conformant	Yes	Product Environmental Profile Yes		
Technical Information				
Voltage	600 V			