

## $Wire mold \label{eq:wiremold} {\bf Plug-In~Outlet~Center~Unit~/~Rack~Mount~120V/15A/6~rear~O/L~/lighted~switch/6'~cord/Computer~Grade~Surge~Part~No.~R5BZX}$



Six rear outlets, 15A. 6' (1.8m) cord. Perma Power computer grade, surge protection.

## Features & Benefits

Six rear outlets, 15A. 15' (4.6m) cord. Perma Power computer grade, surge protection.

## Specifications

Genera	1 1-1-	

Product Line	Wiremold	UPC Number	786776012224		
Country Of Origin	Mexico	Application Sector	Residential/Commercial		
Standard	cULus Recognized: File E66421: Guide XBYS2, XUHT2, VZCA8	Туре	PIOC		
Dimensions					
Product Width US	19.0 in	Product Height US	2.57 in		
Product Length US	1.75 in				
Buy American Act Compliance					

NAFTA Yes

## Technical Information

Phase	Single Stage	Frequency Rating	+35dB Hz
Connection	Cord-ended	Class	75
Amperage	15 A	Short Circuit Rating	36000 Amps [12000 Amps L-N 12000 Amps L-G 12000 Amps N-G]
Response Time	<1 ns	Mounting Type	Rack Mounting
Mounting	Yes	Type of Indicators	Light
Voltage	120.0 V		