

MPN: 0070-24222-AC

22" 24/7 Full-HD Surveillance monitor for 24/7 use. 1x HDMI 2.0, 1x VGA, 2x BNC inputs. 1x BNC output, 2x Speakers

High Performance 24/7 Security Monitor

When you need a display that lasts, Ernitec delivers with this state-of-the-art monitor. Featuring a BNC input, it's easy to connect your analog camera for seamless integration.

Display Characteristics

- Screen Size: 22 inches
- Active Display Area: 476.64mm (W) × 268.11mm (H)
- Display Mode: 16:9
- LED Type: TFT-LED
- Resolution: 1920 × 1080
- Display Color: 16.7 million
- Pixel Pitch: 0.248mm (H) × 0.248mm (V)
- Brightness: 250 nits
- Contrast Ratio: 1000:1
- Viewing Angle: 178° (H) / 178° (V)
- Response Time: 5ms
- Backlight: LED

Input & Output

- HDMI 2.0: 1
- VGA: 1
- BNC Input: 2
- BNC Output: 1
- Speaker: 2x 3W (Stereo)

Video

- Color System: PAL/NTSC/SECAM
- OSD Control: Auto adjust, Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Color, Language
- 3D Comb Filter: Yes
- Video Noise Reduction: Yes

Power & Mounting

- Power Supply: DC 12V, 50/60Hz
- Working Temperature: -30 to +85°C
- Power Consumption: ≤25W
- Menu Languages: English, French
- Mounting Options: Stand mount, VESA mount
- Weight: 3.5kg
- MTBF: 50,000 hours
- VESA Size: 100x100
- EDID Compatibility: Not compatible

Included Accessories

- Screws
- Cable holder
- Quick start guide

This monitor is designed to provide reliable performance around the clock, making it an ideal choice for security applications.

- 2 BNC input + 1 BNC output



- EU + UK Power cord included

Specifications

Design	Detachable stand	Yes
	Market positioning	Industrial
	Product colour	Black
Display	Aspect ratio	16:9
	Contrast ratio (typical)	1000:1
	Display brightness (typical)	250 cd/m ²
	Display diagonal	22 "
	Display resolution	1920 x 1080 pixels
	Display technology	LCD, LED
	HD type	Full HD
	Native aspect ratio	16:9
	Response time	5 ms
	Viewable size, horizontal	47.7 cm
	Viewable size, vertical	26.8 cm
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	Panel mounting interface	100 x 100 mm
	VESA mounting	Yes
Other features	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 100 x 100
	Dimensions (WxDxH)	506 x 48 x 303 mm
	Mean time between failures (MTBF)	50000 h
	Noise filter	Yes
	Package dimensions (WxDxH)	550 x 108 x 413 mm
	Picture enhancement	DNle digital image processing
	Speakers	2 x 3W Stereo
	Weight	3500 g
Packaging content	Cables included	Power
	Power adapter included	No
	Quick start guide	Yes
	Screws included	Yes
	Stand included	Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	BNC input ports	2

Ports & interfaces	HDMI ports quantity	1
	HDMI version	2.0
	VGA (D-Sub) ports quantity	1
Power	Power consumption (average)	25 W
	Power plug type	C14 coupler
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
19	0070-24219-BNC
22	0070-24222-AC
24	0070-24124-TV
28	0070-24228-AC

Other images

