

MPN: RSL20U61BL

by Logon 19" 20U Rack Cabinet 600 x 1000mm Server Line

Product Dimensions: 600 x 1000 x 1075mm

Free standing rack cabinets offers the most ideal solutions at the offices and system rooms in the areas of cabling and server installations. The cabinets created in a highly strong and robust structure are unrivalled in their class.

With the specially designed structure, the cabinets can be assembled and disassembled easily. Simple tools will be enough to assemble the whole cabinet. The front door with spring loaded hinge system provides ease at the installation and use as it's changeable on the desired direction of opening, removable and installable without the need of any tool.

The standard rear door model is solid metal door. It is easy to remove especially during relocation, installation and maintenance of the cabinet and system inside. The easily removable rear doors have the barrel locking mechanism.

The 3U high brushed cable entries on the bottom and top of the back of the cabinet are provided as the standard configuration of the cabinets. These cable entries enable the cable management on top, back and bottom of the cabinet. As the roof is located 10mm above the top of the cabinet, it not only enables passive ventilation without the assembly of a fan module, but also provides resistance against water and dust.

Cabling Managing Made Easier

The cabinets are designed to enable the integration of vertical cable manager module structurally.

Thus, a bigger cable mass can be managed with these cable managers. The bottom chassis has a wide cable entry. The rubber edged sliding cable entry module directs the mass cables. After the cables are directed inside the cabinet, the sliding part is closed and fixed. The rubber edges are closed without any damage to the cables and the dust proof structure is provided on the maximum level available. Thanks to the Tire-Up structured side bracket provided, it's extra advantageous to direct the cables upwards and downwards and to fix them in the exact position.

Secured Door

The front door modules with horizontally split doors consist of decorative metal frame on both left and right. The front doors with full size, break-resistant, tempered, anti-static 4mm smoke colored glass are lockable by the handle-locking mechanism.

The other sides are strengthened with U and Y shaped lockable and interlock able special metal bars. The rear door is solid metal and is easy to remove especially during relocation, installation and maintenance of the cabinet and system inside.

The easily removable rear doors have the barrel-locking mechanism.

Easy Secure Access from All Sides

The cabinets have the maximum strength with the side brackets and extra cube omega support points.

The side panel of the cabinets are easily removable and have a barrel-locking system. The 42U and 46U high cabinets have vertically split side panels and it enables easy removal of the panels during installation and maintenance or



when there is not enough space available.

- Perforated Door
- Free-Standing
- RAL9005
- Cage nuts can be bought separate
- 4 way fan included

Specifications

Features

Adjustable feet	Yes
Adjustable mounting rails	Yes
Assembly required	No
Back door construction	Perforated
Back door key lock	Yes
Back door style	Grilled
Cable entry point	Yes
Castor wheels	Yes
Cooling type	Active
Dusting brush	Yes
Frame type	Closed
Front door construction	Perforated
Front door key lock	Yes
Front door style	Grilled
Front uprights	Adjustable
International Protection (IP) code	IP20
Key lock	Yes
Material	Steel
Maximum weight capacity	600 kg
Mounting hole shape	Square
Number of fans	4 fan(s)
Preassembled	Yes
Product colour	Black
Rack capacity	20U
Rack rails	Yes
Removable back door	Yes
Removable front door	Yes
Removable side panels	Yes
RoHS compliance	Yes
Side panel construction	Steel
Side panel key lock	Yes
Side panel style	Blind
Side panels included	Yes
Soundproof	No

Features	Stabilising foot screw	Yes
	Type	19" Freestanding Rack
Other features	Compliance industry standards	IEC 60297-3-109, IEC 60297-3-100, IEC 61587-1.
	Dimensions (WxDxH)	600x1000x1075 mm
Vendor information	Brand Name	Lanview
	Warranty	5 Year(s)
Weight & dimensions	Size (imperial)	19 "

Other products in this series

Rack capacity	Black	White
12U	RSL12U61BL	RSL12U61WH
16U	RSL16U61BL	RSL16U61WH
20U	RSL20U61BL	RSL20U61WH
22U	RSL22U61BL	RSL22U61WH
26U	RSL26U61BL	RSL26U61WH
32U	RSL32U61BL	RSL32U61WH
36U	RSL36U61BL	RSL36U61WH
42U	RSL42U612BL	
46U	RSL46U61BL	RSL46U61WH

Other images

