

MPN: 0070-24222-AC-M

22" 24/7 Full-HD Surveillance monitor. Metal chassis design - AC Power

The Ernitec 22" TFT-LED monitor delivers high performance engineered for clarity and uninterrupted performance for 24/7 security use when you want your display to last.

With 5ms response time, a resolution of 1920x1080 and 24-bit color, every image comes to life with great detail fluid motion and seamless transitions.

Equipped with versatile inputs including HDMI 2.0 and VGA. We have even added 2 BNC inputs so you can easily add analog cameras to the monitor.

Features such as 3D comb filter and video noise reduction guarantee sharp, clear visuals.

With robust construction and thoughtful design, it's the ideal choice for professional settings.

VESA size: 100x100

- 2 BNC input + 1 BNC output
- EU + UK Power cord included



Specifications

Design	Detachable stand	Yes
	Housing material	Metal
	Market positioning	Industrial
	Product colour	Black
Display	Anti-glare screen	Yes
	Aspect ratio	16:9
	Colour depth	24 bit
	Contrast ratio (typical)	1000:1
	Display brightness	250 cd/m ²
	Display brightness (typical)	250 cd/m ²
	Display diagonal	22 "
	Display number of colours	16.7 million colours
	Display resolution	1920 x 1080 pixels
	Display technology	LCD, LED
	HD type	Full HD
	Native aspect ratio	16:9
	Pixel pitch	0.248 x 0.248 mm
	Response time	5 ms
	Viewable size, horizontal	47.7 cm
	Viewable size, vertical	26.8 cm
Viewing angle, horizontal	178 °	

Display	Viewing angle, vertical	178 °
Ergonomics	On Screen Display (OSD)	Yes
	On Screen Display (OSD) languages	English, French
	Panel mounting interface	100 x 100 mm
	VESA mounting	Yes
Operational conditions	Operating temperature (T-T)	-30 - +85 °C
Other features	AC adapter included	Yes
	Accessories included	screw, cable holder, quick start guide
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 100 x 100
	Dimensions (WxDxH)	498 x 56 x 309 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 100 x 100 mm
	Noise filter	Yes
	Package dimensions (WxDxH)	635 x 172 x 440 mm
	Picture enhancement	DNle digital image processing
	Speakers	2 x 3W Stereo
	Weight	4100 g
	Packaging content	Cables included
Quick start guide		Yes
Screws included		Yes
Stand included		Yes
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	BNC input ports	2
	HDMI ports quantity	1
	HDMI version	2.0
	VGA (D-Sub) ports quantity	1
Power	AC input voltage	230V V
	Power consumption (average)	25 W
	Socket connector type	C13
Technical details	Warranty period	5 year(s)
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
8	0070-24108-M
10.1	0070-24110-M-L
19	0070-24119-M
22	0070-24222-AC-M
32	0070-24232-M
43	0070-24143
49	0070-24149
55	0070-24155
65	0070-24165
75	0070-24175
86	0070-24186
98	0070-24198

Other images

