

MPN: MO-G-SFP-BX-U-40KM

# SFP 1 Gbps, SMF, 40 km, LC, DDMI support, Compatible with Generic SFP-BX-U-40KM

Micro-Optics products provide seamless connectivity for all your current and future network hardware needs.

- **\*\*100% Generic Compatible\*\***



## Specifications

<b>Features</b>	<b>Certification</b>	MSA
	<b>Compatible products</b>	Generic SFP-BX-U-40KM
	<b>Easy to install</b>	Yes
	<b>Form factor</b>	SFP
	<b>Plug and Play</b>	Yes
	<b>RoHS compliance</b>	Yes
<b>Operational conditions</b>	<b>Operating temperature (T-T)</b>	0 - 70 °C
	<b>Storage relative humidity (H-H)</b>	10 - 85 %
	<b>Storage temperature (T-T)</b>	-40 - 85 °C
<b>Packaging data</b>	<b>Number of products included</b>	1 pc(s)
<b>Performance</b>	<b>Digital Diagnostics Monitoring (DDM)</b>	Yes
	<b>Duplex system</b>	Half
	<b>Ethernet interface type</b>	Gigabit Ethernet
	<b>Fiber optic connector</b>	LC
	<b>Fiber ports quantity</b>	1
	<b>Interface type</b>	SFP
	<b>Maximum data transfer rate</b>	1000 Mbit/s
	<b>Maximum transfer distance</b>	40000 m
	<b>Maximum transfer distance (Single-mode)</b>	40000 m
	<b>Multi-mode fiber (MMF) supported</b>	No
	<b>Rx wavelength (min)</b>	1550 nm
	<b>SFP transceiver standard</b>	BX-U
	<b>SFP transceiver type</b>	Fiber optic

<b>Performance</b>	<b>Single-mode fiber (SMF) supported</b>	Yes
	<b>Tx wavelength (min)</b>	1310 nm
<b>Vendor information</b>	<b>Brand Name</b>	Lanview
	<b>Warranty</b>	3 Year(s)
<b>Weight &amp; dimensions</b>	<b>Package type</b>	White box

## Other images

