

MPN: 0070-24228-AC

## 28" 24/7 4K UHD Surveillance monitor.

3x HDMI 2.0, 1x Display Port, 2x

### Speakers

#### DISPLAY CHARACTERISTICS

- 4K HD solution
  - Industrial-grade LED screen
  - Designed for CCTV
  - High brightness, high contrast, high definition
  - Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
  - Picture fast response
  - 178° wide viewing angle
  - High fidelity digital processing, brilliant and vivid video
  - 24/7 working status, working continuously for 5 years
  - Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation
  - Menu with convenient Controller
- Not EDID compatible

- 24/7
- Security monitor
- Desktop monitor
- EU + UK Power cord included
- HDMI cable included



## Specifications

<b>Design</b>	<b>Detachable stand</b>	Yes
	<b>Market positioning</b>	Industrial
	<b>Product colour</b>	Black
<b>Display</b>	<b>Aspect ratio</b>	16:9
	<b>Contrast ratio (typical)</b>	1000:1
	<b>Display brightness (typical)</b>	350 cd/m <sup>2</sup>
	<b>Display diagonal</b>	28 "
	<b>Display resolution</b>	3840 x 2160 pixels
	<b>Display technology</b>	LCD, LED
	<b>HD type</b>	4K Ultra HD
	<b>Native aspect ratio</b>	16:9
	<b>Response time</b>	5 ms
	<b>Viewable size, horizontal</b>	62.1 cm
	<b>Viewable size, vertical</b>	34.1 cm
	<b>Viewing angle, horizontal</b>	178 °
<b>Viewing angle, vertical</b>	178 °	
<b>Ergonomics</b>	<b>Panel mounting interface</b>	100 x 100 mm
	<b>VESA mounting</b>	Yes

<b>Other features</b>	<b>Certification</b>	EMC Class A
	<b>Comb filter</b>	3D
	<b>Compatible wall mount</b>	Vesa 100 x 100
	<b>Dimensions (WxDxH)</b>	659 x 64 x 380 mm
	<b>Mean time between failures (MTBF)</b>	50000 h
	<b>Mounting</b>	VESA mount 100 x 100 mm
	<b>Package dimensions (WxDxH)</b>	715 x 130 x 500 mm
	<b>Picture enhancement</b>	DNle digital image processing
	<b>Speakers</b>	2 x 3W Stereo
	<b>Weight</b>	4800 g
<b>Packaging content</b>	<b>Cables included</b>	HDMI, Power
	<b>Quick start guide</b>	Yes
	<b>Screws included</b>	Yes
	<b>Stand included</b>	Yes
<b>Performance</b>	<b>Operating hours (hours/days)</b>	24/7
<b>Ports &amp; interfaces</b>	<b>AC (power) in</b>	Yes
	<b>DisplayPorts quantity</b>	1
	<b>HDMI ports quantity</b>	3
	<b>HDMI version</b>	2.0
<b>Power</b>	<b>AC input frequency</b>	50/60 Hz
	<b>AC input voltage</b>	100-240 V
	<b>Power consumption (average)</b>	40 W
	<b>Power plug type</b>	C14 coupler
	<b>Power supply type</b>	Industrial
	<b>Socket connector type</b>	C13
<b>Vendor information</b>	<b>Brand Name</b>	Ernitec
	<b>Homepage</b>	<a href="http://www.ernitec.com">http://www.ernitec.com</a>
	<b>Warranty</b>	5 Year(s)

## Other products in this series

Display diagonal	
19	0070-24219-BNC
22	0070-24222-AC
24	0070-24124-TV
28	0070-24228-AC

Other images

