

Product datasheet

Specifications



APC KVM 2G, Server Module, USB with Virtual Media and CAC

KVM-USBVMCAC

EAN Code: 0731304286707

Main

Product or component type Server

Physical

Height 14 mm

Width 125 mm

Depth 125 mm

Product weight 0.14 kg

Mounting preference No preference

Mounting mode Not rack-mountable

Conformance

Product certifications C-Tick
CE
TAA compliance
VCCI class A

Standards FCC part 15 class A
ICES-003
UL 60950-1

Environmental

Ambient air temperature for operation 0...50 °C

Operating altitude 0...10000 ft

Relative humidity 5...95 %

Ambient air temperature for storage -10...60 °C

Storage altitude 0...15240 m

Storage Relative Humidity 5...95 %

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 4.2 cm

Package 1 Width 12.9 cm

Package 1 Length 12.5 cm

Package 1 Weight 0.18 kg

SCC14 10731304286704

Logistical informations

Country of origin TW

Contractual warranty

Warranty (in months) 24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.6 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

