MPN: 0070-24155-L

55" 24/7 4K UHD surveillance monitor - plastic frame



Product Feature
4K HD Solution
Using all-imported industrial-grade LED screen, Designed for CCTV.
High brightness, High contrast, High definition.
Adapt newest 3D digital filtering and 3D digital noise reduction technology.
Picture fast response; 178 ° wide viewing angle; Ensure that the image display is not deformed.
7/24 working Status; Continue working 5 years.
Metal chassis design, Anti-static, Anti-magnetic field, Anti-interference, no radiation.
Humanize Menu; Convenient Controller.

Screen Size 55"
Active Display Area (mm) 1209.6mm(W)×680.4mm(H)
Display Mode 16:9
LED Type TFT-LED
Resolution 3840 × 2160
Display Color 1.073G
Pixel Pitch(mm) 0.315(H)×0.315(V)
Brightness(nits) 450cd/M 2
Contrast Ratio 4000:1
Viewing Angle 178(H) /178(V)
Response Time 5ms
Backlight LED

INPUT&OUTPUT
HDMI 2.0 x 3
DP x 1
USB x 1
Power x 1
Speaker 2x3W(Stereo)

VIDEO
PAL/NTSC/SECAM
Auto adjust, Brightness, Contrast, Hori. / Vert. Position, Clock, phase, Color, Language..

POWER&Mount Way
AC100V~240V,50/60Hz
-30 to +85 □
50W
English(other languages supported)
Stand mount, VESA mount
50000Hours

VESA size: 400 x 200

Specifications

Battery	**Battery Weight (g)**	3 g
	Lithium Weight (g)	0.7 g
Design	**Front bezel colour**	Black

Design	**Product colour**	Black
Display	**3D**	Yes
	Aspect ratio	16:9
	Backlight type	LED
	Display brightness	450 cd/m²
	Display diagonal	55 "
	Display number of colours	1.073 billion colours
	Display resolution	3840 x 2160 pixels
	Display technology	LCD, LED
	HD type	4K Ultra HD
	Native aspect ratio	16:9
	Pixel pitch	0.315(H)×0.315(V) mm
	Response time	5 ms
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	**On Screen Display (OSD)**	Yes
	On Screen Display (OSD) languages	English
	Panel mounting interface	200 x 200 mm
	VESA mounting	Yes
Legal Information	**ADR Information**	UN3091 - Lithium METAL (inside equiment)
	Country of Origin	China
	Tariff No.	8528529100
	UNSPSC Code	43211902
Operational conditions	**Operating temperature (T-T)**	-30 - +85 °C
Other features	**AC adapter included**	Yes
	Accessories included	Industrial PSU,Screw, Cable holder, Quick start guide
	Active display area (W x H)	1209.6mm(W)×680.4mm(H) mm
	Analog signal format system	PAL, NTSC, SECAM
	Certification	EMC Class A
	Contrast ratio	4000:1
	Dimensions (WxDxH)	1248 x 69 x 730 mm
	Mean time between failures (MTBF)	50000 h
	Mounting	Stand mount, VESA mount 200 x200 mm
	Noise filter	Yes
	Number of colours	1.073 billion colours
	Package dimensions (WxDxH)	1335 x 182 x 820 mm
	Power consumption	50 W
	Speakers	2 x 3W (Stereo)
	USB ports quantity	1

Other features	**Weight**	12500 g
Package dimensions	**Depth (package,cm)**	18.2 cm
	Gross Weight (Package, kg)	16.2 kg
	Height (package,cm)	82 cm
	Width (package,cm)	133.5 cm
Performance	**Operating hours (hours/days)**	24/7
Ports & interfaces	**DisplayPorts quantity**	1
	HDMI	Yes
	HDMI ports quantity	3
	HDMI version	2.0
Power	**AC input frequency**	50/60 Hz
	AC input voltage	100-240 V
	Socket connector type	C13
Product dimensions	**Net Weight (Product, kg)**	12.5 kg
	Product Depth	6.9 cm
	Product Height	73 cm
	Product Width	124.8 cm
Vendor information	**Brand Name**	Ernitec
	Warranty	5 Year(s)

Other images



