

MPN: 0070-24232-WATERPROOF

32" 24/7 FHD Surveillance monitor. Metal chassis design - Water & vandal proof. 1x HDMI, 1x VGA, 1x BNC out, 2x BNC IN

0070-24232-WATERPROOF is a professional-grade display designed for reliable operation in demanding environments. With FHD resolution, it delivers sharp and detailed image quality for commercial and industrial applications.

The front is rated IP67 and IK10, providing strong protection against water, dust, impacts, and vandalism. The rear is rated IP22 and must be installed in a protected area to avoid direct exposure to humidity, rain and wind. Ideal for installations where the front is exposed while the rear remains sheltered, such as in enclosures or under canopies.



Key Benefits:

- FHD – crisp, high-resolution visuals
- IP67 front – resistant to water and dust
- IK10 front – impact and vandal-resistant
- Reliable performance – built for professional use

Important Installation Notes:

- The rear (IP22) must be protected from direct rain and water exposure
- Recommended installation in enclosures, recesses, or under cover
- Suitable for indoor use and controlled outdoor environments

Typical Applications:

- Industrial installations
- Outdoor solutions with protected mounting
- Technical rooms and infrastructure setups
- Installations requiring front-side environmental protection

- 24/7 display
- Security monitor
- EU + UK Power cord included
- HDMI cable included
- VESA size: 200x200
- Waterproof IP65 in front and IP22 on connectors
- Vandalproof on the front IK10
- Must be built-in to protect IP22 back side
- 5 years warranty

Specifications

Design	Market positioning	Industrial
	Product colour	Black
	Protection features	Vandal proof, Waterproof
Display	Aspect ratio	16:9
	Contrast ratio (typical)	1300:1
	Display brightness (typical)	350 cd/m ²

Display	Display diagonal	32 "
	Display resolution	1920 x 1080 pixels
	Display technology	LCD, LED
	HD type	Full HD
	Native aspect ratio	16:9
	Response time	5 ms
	Viewing angle, horizontal	178 °
	Viewing angle, vertical	178 °
Ergonomics	Panel mounting interface	200 x 200 mm
	VESA mounting	Yes
Other features	Brightness	350 cd/m ²
	Certification	EMC Class A
	Comb filter	3D
	Compatible wall mount	Vesa 200 x 200
	Dimensions (WxDxH)	736 x 88 x 440 mm
	Display language	English
	Glass protection	Yes
	Mean time between failures (MTBF)	50000 h
	Mounting	VESA mount 200 x 200 mm
	Package dimensions (WxDxH)	875 x 197 x 570 mm
	Picture enhancement	DNle digital image processing
	Power consumption (max)	40 Watt
	Power cord included	Yes
	USB ports quantity	1
	Weight	11500 g
Packaging content	Quick start guide	Yes
	Screws included	Yes
	Stand included	No
Performance	Operating hours (hours/days)	24/7
Ports & interfaces	AC (power) in	Yes
	BNC input ports	2
	HDMI ports quantity	1
	HDMI version	2.0
	VGA (D-Sub) ports quantity	1
Power	Power consumption (average)	40 W
	Socket connector type	C13
Vendor information	Brand Name	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	5 Year(s)

Other products in this series

Display diagonal	
10	0070-24110-WATERPR OOF
22	0070-24122-WATERPR OOF
24	0070-24224-WATERP ROOF
27	0070-24127-WATERPR OOF
32	0070-24232-WATERP ROOF
43	0070-24143-WATERP ROOF-L
55	0070-24250-WATERP ROOF
65	0070-24265-WATERP ROOF
75	0070-24275-WATERP ROOF
86	0070-24286-WATERP ROOF

Other images

