


Wiremold 5' All USB Aluminum Plugmold® Multioutlet System Part No. AL20USB512



Available in 5' (1.5m) length with 12'' spacing. USB is 2.4 Amps (shared between two ports) 5VDC. .040'' (1.0mm) aluminum housing. Packed two per carton. Each unit supplied with one (1) Coupling and two (2) Blank End Fittings.

## Features & Benefits

USB charging. Dual-port charging modules share 2.4 amps of charging Compact design. Low-profile design installs in capacity and can charge multiple phones, tablets or other mobile devices at the same time. Compact design. Low-profile design installs in tight locations while offering multiple USB charging connections.

## Specifications

## General Info

Product Line	Wiremold	UPC Number	786776184310
Country Of Origin	United States	Number of Receptacles	5
Application Sector	Commercial	Standard	cULus Listed Multioutlet Assembly: File E15191 Guide PVGT
Туре	Plugmold		
Listing Agencies / 3rd P	Party Agencies		
cULus ListingNumber	E15191	cULus Listed	Yes
Buy American Act Comp	liance		
NAFTA	Yes		
Additional Information			
RoHS Conformant	Yes	Product Environmental Prof	ile Yes

## Technical Information

Frequency Rating	60 Hz	Amperage	13 A
Enclosure Type	Aluminum	Voltage	125.0 V
Environmental Conditions	Dry interior locations		