

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio GSA/TAA

One device. Many possibilities.

Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.



*Product image may differ from actual product

Poly signature audio

Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.

One-touch join

All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio GSA/TAA

Specifications



Display

Aspect ratio: 16:9
Native resolution: 720 x 1280
Panel technology: Color LCD
Display size (diagonal): 5"
Display size (diagonal, metric): 12.7 cm (5")
Touch-enabled: Gesture-based, multi-touch capable touchscreen

Connectivity and communications

Wireless range: Up to 6.1 m
Wireless range (Imperial): Up to 20 ft
External I/O ports:
1 USB 2.0 Type-A (for USB battery charging)
1 USB 2.0 Micro-B (for USB audio device)
2 RJ-45 (10/100/1000BASE-TX Mbps)
Wireless technologies:
Bluetooth® 4.2
Wi-Fi network connectivity: 2.4-2.4835 GHz (802.11b, 802.11g, 802.11n HT-20)
5.15-5.825 GHz (802.11a, 802.11n, HT-20, 802.11n HT-40)

Battery

Power features:
LAN IN: Built-in auto-sensing IEEE 802.3at, PoE Device (Class 4)
LAN OUT: Built-in auto-sensing IEEE 802.3af power sourcing equipment¹

User interface features

Languages:
Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:
Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
Comfort noise generation
DTMF tone generation (RFC 2833 and in-band)
Low delay audio packet transmission
Adaptive jitter buffers
Microphone type: Three cardioid microphones
Frequency response (microphone): 100 Hz to 22 kHz
Sensitivity (speaker): 92 dB
Audio codecs:
G.711 (A-law and μ -law)
G.722
G.722.1
G.722.1C
G.729AB
G.719
Polycom® Siren™ 7
Siren™ 14
iLBC
OPUS

Environmental

Certifications and compliances: AS/NZS 60950-1; AS/NZS 62368-1:17; Australia -AS/NZ 4268; Australia A&C Tick; CAN/CSA C22.2 No. 60950-1-03; CAN/CSA C22.2 No. 62368-1:14; CE Mark; CISPR22 Class B; EN 301 489-1, EN 301 489-3, EN 301 489-17; EN 61000-3-2; EN 61000-3-3; EN 62368-1; ETSI EN 300 328 v1.9; ETSI EN 300 330; ETSI EN 301 893 v1.7; FCC Part 15 (CFR 47) Class B; FCC Part 15.225; FCC Part 15.247; FCC Part 15.407; ICES-003 Class B; IEC 60950-1; IEC 62368-1; Japan Item (19); Japan Item (19)-3; Japan Item (19)-3-2; Japan MIC/VCCI Class B; NZ Telepermit; ROHS compliant; RSS 247 Issue 1; UL 60950-1; UL 62368-1
Operating humidity range: 5 to 95%
Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / 32 to 104°F
Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -20 to 70 °C / -40 to 158°F
Energy star certified: ENERGY STAR® certified

Certifications

Certified collaboration software: Microsoft Teams; Skype for Business; Zoom
Special features:
Unicode UTF-8 character support

Applications supported

Management software:
Poly Zero Touch Provisioning
RealPresence Resource Manager (v.10.1 or above) based provisioning
Polycom Device Management Service for Enterprise (PDMS-E)
Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management
SDP

Display features

On-screen virtual keyboard

Security

Security management:
802.1X Authentication and EAPOL Media encryption via SRTP
Digest authentication
Encrypted configuration files
HTTPS secure provisioning
Password login
Support for signed software executables
Support for URL syntax with password
Transport Layer Security (TLS)
Wi-Fi encryption: WEP; WPA-Personal, WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP-MSCHAPv2)
FIPS 140-2 compliant cryptographic module

Network

Supported network protocols:
DHCP VLAN discovery
LLDP-MED for VLAN discovery
FTP/TFTP/HTTP/HTTPS server-based central provisioning
Manual or dynamic host configuration protocol (DHCP) network setup
QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DHCP
Time and date synchronization using SNTP
Provisioning and call server redundancy support
VoIP features:
IETF SIP (RFC 3261 and companion RFCs)

Poly Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio GSA/TAA

Specifications



Headset and handset compatibility

Headset and handset compatibility:

Bluetooth® headset compatibility

Telephony and call handling features

Telephony and call handling features:

Bundled with Polycom UC Software: Corporate Directory Access using LDAP

Call timer and call waiting

Call transfer, hold, divert (forward), park, pickup

Called, calling, connected party information

Distinctive incoming call treatment/call waiting

Do not disturb function

Local configurable digit map/dial plan

Local five-way audio conferencing

Shared call/bridged line appearance

Visual Conference Management

Up to 3 lines (maximum one Skype for Business and Microsoft Teams)

Daisy-chain up to four

One-touch speed dial, redial and meeting join

Weight and dimensions

Product Primary Color: Black

Weight (Imperial): 21 lb

Weight (metric): 950 g

Product dimensions (Imperial): 15.1 x 2.9 x 13.1 in

Product Dimensions (metric): 38.3 x 7.5 x 33.2 cm

Package dimensions (Imperial): 19 x 4.5 x 15.5 in

Package dimensions (metric): 48.3 x 11.5 x 39.4 cm

Package weight (Imperial): 4.3 lb

Package Weight (metric): 1970 g

UPC number: 197497515701

Product number: 84C21AA

Warranty

Poly standard one-year limited warranty

What is in the box

Console

Network (LAN) cable-CAT-5E

USB Type-A cable

Cable wrap

Tactile overlay for improved accessibility

Setup sheet

Technical Specifications Footnotes

¹ Requires full Class 4 power input on LAN IN for operation