

Poly VVX 250 4-Line IP Phone and PoE-enabled GSA/TAA

For today's office

Quality sound is standard on the Poly VVX 250 IP desk phone. You'll appreciate all the smart features on non-stop call days, but equally love the color display. It's a win-win for today's office environments.



*Product image may differ from actual product

Conversations stay on track

Hear every nuance on the Poly VVX 250 IP desk phone with quality audio featuring Poly HD Voice. And reduce distracting background noise at the source with Poly Acoustic Fence technology.

Integrated protection¹

Your phones stay cleaner for longer with integrated Microban® antimicrobial product protection¹ actively reducing the growth of bacteria 24/7.

Poly VVX 250 4-Line IP Phone and PoE-enabled GSA/TAA

Specifications



Display

Native resolution: 320 x 240
Panel technology: Color LCD
Display size (diagonal): 2.8"
Display size (diagonal, metric): 71 cm (2.8")

Connectivity and communications

External I/O ports:
1 USB 2.0 Type-A (for media, storage applications, headset, optional Wi-Fi adapter)
2 RJ-45 (10/100/1000BASE-TX Mbps)

Battery

Power features:
Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 2)
4.5 W (maximum)³

User interface features

Languages:
Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:
Poly HD Voice
Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression
Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset
Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio in/out to use the phone's handset, optional headset and handsfree speakerphone with PC applications
Individual volume settings with visual feedback for each audio path
Voice activity detection
Comfort noise generation
DTMF tone generation (RFC 2833 and in-band)
Low delay audio packet transmission
Adaptive jitter buffers
Frequency response (microphone): 150 Hz to 7 kHz
Audio codecs:
G.711 (A-law and μ -law)
G.722
G.729AB
iLBC
OPUS

Environmental

Certifications and compliances: Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-14EN 60950-1; EN 60950-1 & EN 62368-1; EN55024; EN55032 Class B; EN61000-3-2, EN61000-3-3; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; IEC 60950-1 & IEC 62368-1; NZ Telepermit; ROHS compliant; So. Korea KC; So. Africa ICASA; Saudi Arabia CITC; UAE TRA; UL 60950-1 and UL 62368-1; VCCI Class B; Indonesia SDPP; ISPR32 Class B; Korea KCC; LLDP-MED for VLAN discovery; Mexico NOM ANCE; RTP support; Russia CU
Operating humidity range: 5 to 95%
Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / 32 to 104°F
Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -40 to 70°C / -40 to 158 °F
Energy star certified: ENERGY STAR® certified

Certifications

Special features:
Adjustable desk stand (2 positions)
Unicode UTF-8 character support²

Applications supported

Management software:
Poly Lens
Poly Zero Touch Provisioning
Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management
SDP

Display features

Digital picture frame

Security

Security management:
8021X Authentication and EAPOL Media encryption via SRTP
Digest authentication
Encrypted configuration files
HTTPS secure provisioning
Password login
Support for signed software executables
Support for URL syntax with password
Transport Layer Security (TLS)
SRTP media encryption using AES 256 bits

Network

Supported network protocols:
10/100/1000 Base-TX across LAN and PC ports
Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment
Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation
Manual or dynamic host configuration protocol (DHCP) network setup
VoIP features:
Up to 16 SIP line registrations with pagination key
IETF SIP (RFC 3261 and companion RFCs)

Poly VVX 250 4-Line IP Phone and PoE-enabled GSA/TAA

Specifications



Headset and handset compatibility

- Headset ports:**
- 1 RJ-9
 - 1 Electronic Hook Switch (EHS) port for optional adapter
- Headset and handset compatibility:**
- Compatible with commercially available TTY adapter equipment
 - Compliant with ADA Section 508 Subpart B 1194.23 (all)
 - Hearing aid compatibility to ITU-T P.370 and TIA 504A standards
 - Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids

Telephony and call handling features

- Telephony and call handling features:**
- 4 line keys
 - Up to 16 line key assignments for lines, contacts, and features supported with pagination
 - Busy Lamp Field (BLF)
 - Call timer and call waiting
 - Call transfer, hold, divert (forward), park, pickup
 - Called, calling, connected party information
 - Calling Party Identification (RFC8225 classifications – Trusted, Unknown, SPAM)
 - Distinctive incoming call treatment/call waiting
 - Do not disturb function
 - Electronic hook switch capable
 - Enhanced Feature Keys make powerful feature shortcuts online key appearances or soft keys
 - Local three-way audio conferencing
 - Local configurable digit map/dial plan
 - One-touch speed dial, redial
 - Remote missed call notification
 - Reverse number lookup via LDAP
 - Shared call/bridged line appearance
 - Flexible line appearance (one or more line keys can be assigned for each line extension)¹

Weight and dimensions

- Product Primary Color:** Black
- Package dimensions (Imperial):** 9.25 x 9.17 x 2.2 in
- Package dimensions (metric):** 23.5 x 23.3 x 5.6 cm
- Package weight (Imperial):** 1.96 lb
- Package Weight (metric):** 890 g
- UPC number:** 196188445549
- Product number:** 89B64AA

Warranty

Poly standard one-year limited warranty

What is in the box

- Console
- Desk stand/wall mount hardware
- Handset with handset cord
- Network (LAN) cable-CAT-5E
- Setup sheet

Key Selling Points Footnotes

¹ Microban antimicrobial product protection is a built-in active ingredient that enables products to resist the growth of microbes such as bacteria, mold, and mildew. Microban protection helps products stay cleaner, fresher, and last longer than products with untreated surfaces.

Technical Specifications Footnotes

¹ Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features. ² Optional wall mount kit can be ordered separately. ³ External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).