



# 2m Cat.6A S/FTP LSZH Cable, Yellow

No.: 47864

RJ45, M/M, 500MHz, Copper

#### Description

Twisted Pair Patch Cable with RJ45 connectors

Cat.6A S/FTP PIMF, LSZH

Integrated snagless connector for latch protection

Gold plated pins for better conductivity and elimination of signal loss

10 year warranty

Cat.6A S/FTP network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 10 GBase-T.

Cat.6A cable, shielded with braid as overall shield and foil shield for the individual wire pairs (S/FTP). Cat.6A cables meet the requirements of 10 Gigabit Ethernet (10GBaseT) with an operating frequency of up to 500MHz. These cables are manufactured and tested according to the ISO/IEC 11801 specification. The cables are packaged individually in a polybag.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.

The halogen-free sheath material of the LSZH cable makes the product suitable for use in public spaces with its low smoke emission and elimination of toxic halogen emissions.

Available lengths: 0.3m, 0.5m, 1m, 1.5m, 2m, 3m, 5m, 7.5m, 10m, 15m, 20m, 30m.

Available colours: Black, Blue, Grey, Red, White, Yellow, Green

#### Technical details

#### Connectors

Connector A: RJ45 Male Connector B: RJ45 Male Housing Material: Polycarbonate Connector Plating: Nickel Pin Construction: Brass Pin Plating: Gold plated

Dimensions (approx.) WxDxH: 11.6x21.5x8.3mm (0.46x0.85x0.33in)

Cable Construction Length: 2m (6.56ft) Colour: Yellow Type: Cat.6A

Jacket Diameter: 6.0mm (0.24in)

Jacket Material: LSZH Conductor Material: Copper Conductor Gauge: 27AWG Shielding: Aluminium Braid

#### **Specifications**

Supported Bandwidth: 500MHz

Nominal Attenuation: 49.3dB/100m @ 500MHz

Minimum Bend Radius: 72mm (2.84in)

Operating Temperature:  $-10^{\circ}\text{C} - 60^{\circ}\text{C}$  (14F - 140°F) Storage Temperature:  $-20^{\circ}\text{C} - 75^{\circ}\text{C}$  (-4F - 167°F)

### Miscellaneous

Packaging Type: Polybag Warranty (Years): 10

Product Compliance: RoHS, REACH

## **Purchasing Information**

No.: 47864

EAN: 4002888478649

#### This product is also available in other lengths:

47860 - 0.3m (0.98ft) 47861 - 0.5m (1.64ft) 47862 - 1m (3.28ft) 47863 - 1.5m (4.92ft) 47864 - 2m (6.56ft) 47865 - 3m (9.84ft) 47866 - 5m (16.44ft)

47867 - 7.5m (24.61ft)

47868 - 10m (32.81ft) 47869 - 15m (49.21ft)

47870 - 20m (65.62ft)

47871 - 30m (98.43ft)

#### © LINDY 2025