



## Active holder for fixed installation

Fits devices with Protective Boot (EDA10A-RB-0) and without Rotating Hand Strap (EDA10A-HS-1PK). USB Host Type-A. With Easy-switching system. 2,5A charger via pogo pins. 12/24 Volt. With AMPS, VESA 75.

Item no: 713392

EAN Number: 7320287133929

Use an active holder for your EDA10A while driving and you will always have a freshly charged battery! The active holder is to be connected inside the dashboard. It provides a discreet and neat installation without any cables hanging over the interior. Safe and convenient! 12/24 Volt. The product is E-approved. Connect the power cable with a 2A fuse. 2,5A charger. Charging via pogo plug. Professional installation recommended. The holder is equipped with a USB-Host port so you can connect an accessory.

### Easy-switching system:

The easy-switching system enables you to upgrade the holder only, and keep the installed cables. It saves you a lot of time! When upgrading to a new device, you do not longer need to make a full installation. Same goes for maintenance in case of warranty or damage. You simply disconnect the holder from the charging cable via the Molex 6-pin quick connector, and then connect the new holder. The switch is done in a few seconds.

An installation of a tablet onto a vehicle's dashboard is always done on the customer's own responsibility. Brodit recommends to use tablets on the car's headrest, installed onto a Brodit headrest mount.

### Fits the following models:

Honeywell EDA10A

For a complete list, see

[www.brodit.com/en/product/713392](http://www.brodit.com/en/product/713392)

### Charging specifications:

- Input voltage: DC/10-30V
- Charging voltage: DC/4.75-5.3V
- Output current (Typ): 2.5A
- Input & output protection: Input polarity reversal/Output over voltage/Output over current/Output shortprotection
- LED charging indicator: Power input indicator(Green), Ovp/Ocp/Output short (Red)
- Operating temperature: 0°C ~ +40°C
- Storage temperature: -20°C ~ +60°C
- RoHS compliant: CE, E-mark, FCC, RoHS