


## Key Features

- 2K QHD 2560 X 1440 resolution
- SuperClear® IPS panel
- 100Hz Variable refresh rate delivers fluid visuals
- 1ms (MPRT) response time for precision
- HDR10 Delivers Stellar Contrast and Color Accuracy



## Product Description

The ViewSonic VA2708-2K-HD is a 27" QHD monitor featuring HDMI and DisplayPort inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering are delivered through variable refresh rate, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at a low power consumption.



1. VESA Compatible(Wall Mount 75 x 75mm)
2. Joy Key
3. Power In
4. HDMI\*2
5. DisplayPort
6. Audio Out



## DISPLAY

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	2560 x 1440
Resolution Type:	QHD (Quad HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
High Dynamic Range:	HDR10
Light Source:	LED
Brightness:	250 cd/m <sup>2</sup> (typ)
Colors:	16.7M
Color Space Support:	8 bit true
Aspect Ratio:	16:9
Response Time (MPRT):	1ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Software solution
Flicker-Free:	Yes
Color Gamut:	NTSC: 80% size (Typ) sRGB: 111% size / 99% coverage (Typ)
Pixel Size:	0.233 mm (H) x 0.233 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

## COMPATIBILITY

PC Resolution (max):	2560x1440
Mac® Resolution (max):	2560x1440
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	2560x1440

## CONNECTOR

3.5mm Audio Out:	1
HDMI 2.0 (with HDCP 2.2):	2
DisplayPort:	1
Power in:	DC Socket (Center Positive)

## POWER

Eco Mode (Conserve):	22W
Eco Mode (optimized):	26W
Consumption (typical):	30W
Consumption (max):	32W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

## ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

## CONTROLS

Physical Controls:	Up, Right, Down, Left, Power
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

## OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

## WALL MOUNT

VESA Compatible:	75 x 75 mm
------------------	------------

## INPUT SIGNAL

Frequency Horizontal:	30 ~ 150KHz
Frequency Vertical:	48 ~ 100Hz

## VIDEO INPUT

Digital Sync:	TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.4)
---------------	--

## ERGONOMICS

Tilt (Forward/Back):	-5° / 15°
----------------------	-----------

## WEIGHT (IMPERIAL)

Net (lbs):	9
Net Without Stand (lbs):	7.3
Gross (lbs):	12.1

## WEIGHT (METRIC)

Net (kg):	4.1
Net Without Stand (kg):	3.3
Gross (kg):	5.5

## DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	26.6 x 18 x 4.2
Physical (in.):	24.14 x 17.71 x 7.48
Physical Without Stand (in.):	24.14 x 14.29 x 2.08

## DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	676 x 458 x 107
Physical (mm):	613.19 x 449.89 x 190
Physical Without Stand (mm):	613.19 x 362.99 x 52.74

## GENERAL

Regulations:	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, VCCI, PSE, BIS
--------------	---

PACKAGE CONTENTS:	VA2708-2K-HD x1, HDMI Cable (v2.0; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x1 or 2 (by country) for VSE
-------------------	---

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

