

Product datasheet

Specifications



APC Back-UPS Pro, 2200VA/
1320W, Tower, 230V, 4x Schuko
and 2x IEC C13 outlets, RGB
Lights, Pure Sine Wave, Arctic
(White)

BGM2200-GR

⚠ Discontinued

EAN Code: 0731304634775

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Other Input Voltage	230 V
Main Output Voltage	230 V 1 phase
Rated power in W	1320 W
rated power in VA	2200 VA
Product or component type	Uninterruptible power supply (UPS)
Input Connection Type	Schuko
output connection type	4 Schuko surge 2 IEC 60320 C13
Cable length	1.5 m
Number of cables	1
Battery type	Lead-acid battery
Range of product	Back-UPS Pro

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	16 h
Number of battery replacement quantity	1
Battery voltage	24 V
Overcurrent protection	15 A
Battery charger power	12 W rated
Battery life	3...5 year(s)

General

Provided equipment	safety guide USB cable power cable
product web sub-family	Gaming performance
Number preinstalled power module	0
Number of power module free slots	0
Redundant	No

Physical

Colour	White
Height	292.1 mm
Width	104.14 mm
Depth	408.94 mm
Net weight	12.3 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Mounting position	Vertical

Input

Network frequency	50/60 Hz +/- 3 Hz
Plug standard	Schuko
Input voltage limits	168...302 V
Maximum input current	12 A
Switching current capacity	15 A
Input harmonic distortion	Less than 3 % for full load
Input protection type	Circuit breaker

Output

Maximum configurable power in W	1320 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Full load runtime	00:30:00
Half load runtime	00:04:19
Maximum configurable power in VA	2200 VA
Runtime at 700W	00:04:00
Transfer time	8 ms typical : 10 ms maximum

Conformance

Product certifications	CE CB
Equipment protection policy	Lifetime : 50000 euros

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...3048 m
Acoustic level	45 dBA
IP degree of protection	IP20

Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	1080 J
Noise suppression	Full time multi-pole noise filtering : 5% of IEEE surge let-through : zero clamping response time: instantaneous

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.5 cm
Package 1 Width	35.5 cm
Package 1 Length	48 cm
Package 1 Weight	14.52 kg
SCC14	20731304634779

Contractual warranty

Warranty (in months)	24
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 517

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number Ec96232c-7000-4722-846e-a372cdfca8dc

REACH Regulation [REACH Declaration](#)

Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Removable battery User replaceable

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



