

# Delock Serial Cable RS-232 D-Sub9 female to female with narrow plug housing 0.5 m

## Description

This serial cable by Delock is suitable as an **extension cable or connection cable** for modem, printer, measuring instruments, converters, RS232 hubs, patch panels etc. The cable provides the possibility of connecting adjacent systems and devices.

### Mini D-Sub9 connector

These cables fit any RS-232 port, as the **mini D-Sub9 connectors** (44 x 33.3 x 15 mm) are small and compact. In this way, RS-232 connections can be used directly adjacent to each other.



0,5 m

**Item no. 86822**

EAN: 4043619868223

Country of origin: China

Package: Zip poly bag

## Technical details

- Connectors:
  - 1 x serial D-Sub9 female with screws
  - 1 x serial D-Sub9 female with screws
- Cable gauge: 28 AWG
- Pin assignment: 1:1
- Colour: black
- Insulator: PVC
- Screw type: #4-40 UNC
- Cable diameter: ca. 5 mm
- Cable length incl. connectors: ca. 0.5 m

## System requirements

- A free D-Sub9 male

## Package content

- Cable

---

## Images



## General

|                |                    |
|----------------|--------------------|
| Specification: | RS-232 (EIA / TIA) |
| Style:         | Mini Sub-D9        |

## Interface

|              |                                       |
|--------------|---------------------------------------|
| Connector 1: | 1 x serial D-Sub 9 female with screws |
| Connector 2: | 1 x serial Sub-D 9 female with screws |

## Technical characteristics

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Data transfer rate:  | up to 921.6 Kbps                                    |
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND + Shield |

## Physical characteristics

|                               |                                        |
|-------------------------------|----------------------------------------|
| Cable type:                   | AWM Style 2464 28 AWG 80 °C 300 V VW-1 |
| Cable length incl. connector: | 0.5 m                                  |
| Pin finishing:                | gold-plated                            |
| Conductor material:           | Copper tinned                          |
| Conductor gauge:              | 28 AWG                                 |
| Screw type:                   | #4-40 UNC                              |
| Colour:                       | black                                  |
| Cable jacket material:        | PVC                                    |
| Safety of Flammability:       | VW-1                                   |