

Technical Specifications

HP Series 3 Pro FHD Monitor-322pv



Front

1. Power Button
2. Power LED

Technical Specifications

HP Series 3 Pro FHD Monitor-322pv



Back

1. Joypad OSD button	4. HDMI 1.4 Port
2. Security Cable Slot	5. VGA Port
3. Power Connector	

Technical Specifications

Model: 9U5A2AA

Panel Specifications	Display Size (Diagonal)	54.5 cm (21.45")
	Viewable Diagonal Size	54.48 cm (21.45")
	Panel Technology	VA
	Curvature	Flat
	Max Refresh Rate	100 Hz
	Native Resolution	FHD (1920 x 1080)
	Panel Bit Depth	8 bit (6 bit + FRC)
	Aspect Ratio	16:9
	Brightness (Typical)	250 nits
	Display Contrast Ratio (Static)	3000:1
	Display Contrast Ratio (Dynamic)	8M:1
	Flicker Free	Yes (TÜV certified)
	Pixel Pitch	0.2493 x 0.2410 mm
	Pixels Per Inch (PPI)	103 PPI
	Display Colors	Up to 16.7 million colors supported* <small>*Number of colors thru A-FRC technology.</small>
	Backlight Lamp Life Minimum (To Half Brightness - In Hours)	30,000 hours
	Backlight Type	Edge-lit, WLED
	Screen Treatment	Anti-glare
	Hardness	3H
	Haze	25%
	Response Time (Typical)	5ms GtG (with overdrive)
	Horizontal Viewing Angle (Typical Cr>10)	178°
	Vertical Viewing Angle (Typical Cr>10)	178°
	Panel Active Area Metric (W X H)	47.87 x 26.03 cm
	Panel Active Area Imperial (W X H)	18.84 x 10.25 in
	NOTE:	Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
Color	NTSE	72%
Color Management	Color Space	RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2
	RGB Channel Adjust	Yes, Gain
	Integrated Calibration Instrument	No
	Default Color Temperature	Standard (6500K)
Monitor Specifications	Bezel Type	Narrow
	Color Of Stand	Black
	Color Of Head	Black
	Tilt	-5 to +23°
	Vesa Mounting	100 mm x 100 mm
	Security Lock	Security lock-ready
	Detachable Stand	Yes
	Warranty	3/3/0 for LA, NA, EMEA, APJ (3/3/3 in select APJ Countries)

Technical Specifications

Low Blue Light	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
Management Software	HP Client Management Script Library (CMSL)* HP Display Center** * The Client Management Script Library must be downloaded to the connected PC to run CMSL commands. Some limitations may apply to legacy displays. Visit support.hp.com to download HP CMSL. ** Host PC requires Windows 10 and above. HP Display Center is available on the Microsoft store.
On Screen Display (OSD)	On Screen Display Brightness+, Color Control, Image Control, Input Control, Power Control, Menu Control, Management, Information, Exit
	Native Resolution FHD (1920 x 1080) * HDMI 1.4 & VGA required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 1920x1080 at 100 Hz with 8-bit color using one HDMI or DisplayPort™; 1920x1080 at 60 Hz with 8-bit color using one VGA.
	Maximum Resolution Preset Graphic Modes/Supported Resolutions FHD (1920 x 1080 @ 100 Hz) 640 x 480 @ 60Hz 640 x 480 @ 75Hz (HDMI only) 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 800 x 600 @ 75 Hz (HDMI only) 1024 x 768 @ 60 Hz 1024 x 768 @ 75 Hz (HDMI only) 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz 1280 x 1024 @ 60 Hz 1280 x 1024 @ 75 Hz (HDMI only) 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 50 Hz (HDMI only) 1920 x 1080 @ 60 Hz 1920 x 1080 @ 75 Hz (HDMI only) 1920 x 1080 @ 100Hz (HDMI only) Minimum Vertical Scan Rate Maximum Vertical Scan Rate Minimum Horizontal Scan Rate Maximum Horizontal Scan Rate Maximum Pixel Clock User Programmable Modes User-Assignable Function Buttons Languages

Technical Specifications

Connector Types	HDMI	1 HDMI 1.4
	HDCP	Yes, HDMI
	VGA	1 VGA
Special Features	Switch	Monitor Power button Next Active Input / Up button Brightness / Down button Information / Left button Color / Right button Menu / Enter button 11(VGA)/18(HDMI & DisplayPort™)
Power & Operating Specs	Power Supply	Internal
	Power Source	100 – 240 VAC 50/60 Hz
	Power Consumption- Max	22 W
	Energy Saving/Stand By Mode	0.5 W
	Power Consumption - Typical	11 W
Energy Star Data	Operational Mode at 100 VAC	11.3 W
	Operational Mode at 115 VAC	11.2 W
	Operational Mode at 230 VAC	11.1 W
EU Energy Efficiency Class (ErP LOT-5)	On-mode Power Consumption for Standard Dynamic Range (SDR)	12.1 W
EU Energy Efficiency Class (ErP LOT-5)	ErP LOT5 Energy Efficiency Class for Standard Dynamic Range (SDR)	
Operating Conditions	Operating Temperature - Celsius	5~35°C
	Operating Temperature - Fahrenheit	41~95°F
	Non-Operating Temperature - Celsius	-40~65°C
	Non-Operating Temperature - Fahrenheit	-40~149°F
	Operating Humidity	20~80% Relative Humidity (non-condensing)
	Non-Operating Humidity	5~95%RH
	Operating Altitude Metric	0~5,000m (16,400 ft.)
	Non-operating Altitude Metric	0~12,192m (40,000 ft.)
	Operating Altitude Imperial	0~16,400ft
	Non-operating Altitude Imperial	0~40,000ft
Certifications and Compliances	Low Halogen	Yes
	Agency Approvals and Certifications	WW application CE,CB,KC/KCC/NOM/PSB/ICE/TUV-Bauart/ISO 9241-307/TUV flicker free/ TUV LBL/ BIS/ UAE safety/ UAE RoHS/ Ukraine safety/ South Africa safety/ EAC/CSA/PSB/ISC/CCC/CEL/CECP/SEPA/TCO/TCO Certified Edge/Energy Star/ISC/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/CEC/ Works with Chromebook*

Technical Specifications

*This product works with devices capable of running the latest version of ChromeOS and has been certified to meet Google's compatibility standards. Google is not responsible for the operation of this product or its compliance with safety requirements. Chromebook and the Works With Chromebook badge are trademarks of Google LLC.



Microsoft WHQL Certification	Windows 11, Windows 10		
ENERGY STAR® Certified	Yes		
EPEAT® Registered	EPEAT® Gold in United States*		
Regions need to verify by country	*Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.		
China Energy Label	CEL Grade 2		
TCO Certified Edge	Yes		
TCO Certified	Yes		
SmartWay Transport Partnership - NA only	Yes (NA sku)		
Contains Recycled Plastics	85% ITE-derived closed loop plastic*		
Recyclable Packaging (Box, packing materials)	*ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard. Outside Box is 100% sustainably sourced and recyclable* Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable** *100% outer box packaging is made from sustainably sourced certified and recycled fibers. ** Molded pulp cushions are made from 100% recycled wood fiber and organic materials.		
Unit Product/Package Specifications	Product Dimensions (Unpacked with stand) (W x D x H) Product Dimensions (Packed) (W x D x H) Display Head Dimensions (Unpacked without stand) (W x D x H) Base Area Footprint (w x d mm) Bezel Measurements	Metric 50.42 x 18.05 x 38.69 cm 56.7 x 12.1 x 38.7 cm 50.42 x 5.08 x 30.3 cm 174 x 170 mm Top: 16.86 mm Sides: 11.95 mm Bottom: 24.26 mm Product Weight (Unpacked with stand)	Imperial 19.85 x 7.11 x 15.23 in 22.32 x 4.76 x 15.24 in 19.85 x 2.00 x 11.93 in 6.85 x 6.69 in Top: 0.66in Sides: 0.47in Bottom: 0.96 in 6.2 lb

Technical Specifications

Product Weight (Packed)	4.2 kg	9.3 lb
Product Weight (Head Only)	2.4 kg	5.3 lb
Pallet Information	Pallet Dimensions (L x W x H mm)	Slip Sheet: 968 x 1134 x 1935 mm (20' ft & 40' ft) Slip Sheet: 968 x 1134 x 2322 mm (40HQ) Pallet: 968 x 1134 x 2063 mm (20' ft & 40' ft) Pallet: 968 x 1134 x 2450 mm (40HQ)
	Pallet Total Weight	Slip Sheet: 38.11 x 44.65 x 44.65 inch (20' ft & 40' ft) Slip Sheet: 38.11 x 44.65 x 44.65 inch (40HQ) Pallet: 38.11 x 44.65 x 81.22 inch (20' ft & 40' ft) Pallet: 38.11 x 44.65 x 96.46 inch (40HQ)
	Pallet Layers	5 per layer or 6 per layer (slip sheet & pallet)
	Pallet Product per Layer	16 per layer (slip sheet & pallet)
	Total Products per Pallet	80 sets or 96 sets per pallet (slip sheet & pallet)
	Container Load, 20-Foot	960 sets (Slip Sheet and Pallet)
	Container Load, 40-Foot	1920 sets (Slip Sheet and Pallet)
	Container Load, 40-Foot HighQ	2304 sets (Slip Sheet and Pallet)
What's in the box?	AC power cord (1.83m) 5.9ft, HDMI 1.4 cable (1.8m) 5.9 ft, Warranty, Quick Setup Poster	
User Guide and Warranty Languages	User Guide Languages	Arabic, Bahasa Indonesia, Bulgarian, Chinese-S, Chinese-T, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Kazakh, Korean, Latvian, Lithuanian, Norwegian, Polish, Portuguese (Brazilian), Portuguese (Iberian), Romanian, Russian, Serbian, Slovak, Slovenian, Spanish, Swedish, Thai, Turkey, Ukrainian
	Warranty Languages	English US (EN), English AP (EN-AP), English LA (EN-LA), English UK (EN-GB), Arabic (AR) -17x, Bahasa Indonesia (ID), Bosnian (BS), Bulgarian (BG), Chinese-S (CN), Chinese-T (TW), Croatian (HR), Czech (CS), Danish (DA), Dutch (NL), Estonian (ET), Finnish (FI), French Canadian (FC), French European (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JA), Kazakh (KK), Korean (KO), Latvian (LV), Lithuanian (LT), Norwegian (NO), Polish (PL), Portuguese, Brazilian (BR), Portuguese, Iberian (PT), Romanian (RO), Russian (RU), Serbian (SR), Slovak (SK), Slovenian (SL), Spanish, Castilian (ES-ES), Spanish, Latin America (ES-MX),

Technical Specifications

Swedish (SV), Thai (TH), Turkish (TR), Ukrainian (UK),
Vietnamese (VI)

Technical Specifications

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.

Summary

Change Log

Change Log			
December 17, 2024	V1 to V2	Updated	HP Client Management Script Library (CMSL) Footnote
	V2 to V3		
	V3 to V4		