

Blackmagic URSA Cine 12K



Blackmagic URSA Cine 12K is a revolution in digital film with a new large format RGBW 36 x 24mm sensor with larger photo-sites for 16 stops of dynamic range. This revolutionary model also includes interchangeable lens mounts, a dedicated assist station with a second 5" HDR LCD touchscreen, built in ND filters and industry standard Lemo and Fischer connections. Blackmagic URSA Cine comes with a massive 8TB of removable high performance media storage built in and also includes high speed 10G Ethernet and Wifi for fast media upload and syncing to Blackmagic Cloud.

\$14,995

Camera Features

Effective Sensor Size

35.64mm x 23.32mm (Large Format)

Lens Mount

PL mount. Interchangeable with URSA Cine lockable EF mount included.

Lens Control

Active EF and PL mount lens control with compatible lenses.

Dynamic Range

16 Stops

Shooting Resolutions

12,288 x 8040 (12K 3:2 open gate)
 12,288 x 6480 (12K 16:9)
 12,288 x 6912 (12K 17:9)
 12,288 x 5112 (12K 2.4:1)
 9648 x 8040 (12K 6:5)
 9408 x 6264 (9K 3:2)
 8688 x 4896 (9K 16:9)
 9312 x 4896 (9K 17:9)
 9312 x 3864 (9K 2.4:1)
 7680 x 6408 (9K 6:5)
 8192 x 5360 (8K 3:2 open gate)
 8192 x 4608 (8K 16:9)
 8192 x 4320 (8K 17:9)
 8192 x 3408 (8K 2.4:1)
 6432 x 5360 (8K 6:5)
 4096 x 2680 (4K 3:2 open gate)
 4096 x 2304 (4K 16:9)
 4096 x 2160 (4K 17:9)
 4096 x 1704 (4K 2.4:1)
 3216 x 2680 (4K 6:5)

Frame Rates

Project frame rates of 23.98, 24, 25, 29.97, 30, 50, 59.94 and 60 fps supported. Maximum sensor frame rate dependent on resolution selected.

High Speed Frame Rates

12K 3:2 open gate up to 80 fps
 12K 17:9 up to 100 fps
 12K 2.4:1 up to 120 fps
 9K 3:2 Super 35 up to 100 fps
 8K / 4K 3:2 open gate up to 144 fps
 8K / 4K 2.4:1 up to 224 fps

Built in ND Filters

Button activated ND filters with clear, 2-stop, 4-stop and 6-stop IR ND filters.

Focus

Focus button turns on peaking, auto focus available using compatible lenses.

Iris Control

Iris wheel and touchscreen slider for manual iris adjustment on electronically controllable lenses, iris button for instant auto iris settings on compatible lenses so no pixel is clipped in film mode. Scene average auto exposure in video mode.

Screens

2 x Monitoring Screens
1 x Camera Status Screen

Monitoring Screen Dimensions

5 inch.

Monitoring Screen Resolution

1920px x 1080px

Monitoring Screen Brightness

1500 nits.

Monitoring Screen Type

LCD capacitive touchscreen

Metadata Support

Automatically populated lens data from i/Technology with compatible PL, LPL lenses and electronic EF lenses when using optional EF lens mount. Automatic recording of camera settings and slate data such as project, scene number, take and special notes.

Controls

Touchscreen menus on 5 inch screen. Push buttons for other controls. 7 assignable shortcut keys plus 6 assignable shortcut keys on URSA Cine EVF.

Timecode Clock

Highly accurate timecode clock. Less than 1 frame drift every 8 hours.

Connections**Total Video Outputs**

2

SDI Rates

1.5G, 3G, 6G, 12G.

Analog Audio Inputs

2 x XLR analog switchable between mic, line and AES audio. Phantom power support.

Analog Audio Outputs

1 x 3.5mm headphone jack

Reference Inputs

Tri-Sync/Black Burst and Timecode.

Viewfinder

1 x Viewfinder USB-C with power, data, video and locking connector.

Accessories








1 x 7-pin Lemo 'EXT' for power out, serial communication, and run/stop.
1 x 3-pin Fischer 'RS' for power out and run/stop.

Computer Interface

2 x USB Type-C side expansion ports for camera accessories.
Software updates using rear side USB-C.

Ethernet

1 x 10Gb/s RJ-45 connector supporting 10/100/1000/10G BASE-T for Web Media Management, Blackmagic Cloud uploads, camera control and streaming.



Audio

Microphone

Integrated stereo microphone.

Built in Speaker

1 x mono speaker.

Standards

SD Video Standards

None

HD Video Standards

1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60, 1080i50,
1080i59.94, 1080i60

Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

SDI Compliance

SMPTE 292M, SMPTE 424 Level B,
SMPTE 2081-1, SMPTE 2082-1

SDI Audio Sampling

48 kHz and 24 bit

Media

Media

1 x Blackmagic Media Module.

Media Format

Blackmagic

Supported Codecs

Codecs

Blackmagic RAW Constant Bitrate 3:1,
Blackmagic RAW Constant Bitrate 5:1,
Blackmagic RAW Constant Bitrate 8:1,
Blackmagic RAW Constant Bitrate
12:1,
Blackmagic RAW Constant Bitrate
18:1,
Blackmagic RAW Constant Quality Q0,
Blackmagic RAW Constant Quality Q1,
Blackmagic RAW Constant Quality Q3,
Blackmagic RAW Constant Quality Q5.
H.264 Proxy in 1920 x 1080, 8-bit
4:2:0

Control

External Control

Blackmagic URSA Cine EVF can trigger record plus camera functions assigned to the VF1, VF2, VF3, Zoom, Exp and Record buttons. External Camera Control supported using REST API over Ethernet, WiFi or serial communication via the 7-pin Lemo connector. Run / Stop supported via 3-pin Fischer and 7-pin Lemo connector. Blackmagic iPad control and Bluetooth control supported. Blackmagic Zoom Demand and Blackmagic Focus Demand for controlling camera and compatible lenses.

Streaming

Direct Streaming

Supports Secure Reliable Transport (SRT) and Real Time Messaging Protocol (RTMP) local live streaming using a Ethernet or WiFi, or global live streaming using an internet connection via Ethernet, WiFi or USB-C cellular data.

Network Management

NTP

Network time protocol support allows you to sync the time on your camera, whenever connected to a network with any NTP server of your choice.

FTP

Download files from any drive attached to your camera using FTP.

Web Media Manager

Using a browser connected over Ethernet, web media manager allows you to access, browse, download and delete files from any drive connected to the camera.

SMB

File sharing using SMB

Storage Features

Storage Type

1 x Blackmagic Media Module 8TB

Storage Rates

Storage rates based on 24 frames per second.

12K - 12,288 x 8040

Blackmagic RAW 3:1 - 1,194 MB/s

Blackmagic RAW 8:1 - 448 MB/s

Blackmagic RAW 12:1 - 298 MB/s

Blackmagic RAW 18:1 - 199 MB/s

Blackmagic RAW Q0 - 298 to 1,432 MB/s

Blackmagic RAW Q1 - 179 to 716 MB/s

Blackmagic RAW Q3 - 119 to 298 MB/s

Blackmagic RAW Q5 - 90 to 224 MB/s

9K - 9408 x 6264

Blackmagic RAW 3:1 - 713 MB/s

Blackmagic RAW 8:1 - 268 MB/s

Blackmagic RAW 12:1 - 178 MB/s

Blackmagic RAW 18:1 - 119 MB/s

Blackmagic RAW Q0 - 178 to 856 MB/s

Blackmagic RAW Q1 - 107 to 428 MB/s

Blackmagic RAW Q3 - 71 to 178 MB/s

Blackmagic RAW Q5 - 54 to 134 MB/s

8K - 8192 x 5360

Blackmagic RAW 3:1 - 533 MB/s

Blackmagic RAW 5:1 - 320 MB/s

Blackmagic RAW 8:1 - 200 MB/s

Blackmagic RAW 12:1 - 133 MB/s

Blackmagic RAW Q0 - 133 to 319 MB/s

Blackmagic RAW Q1 - 80 to 200 MB/s

Blackmagic RAW Q3 - 53 to 133 MB/s

Blackmagic RAW Q5 - 40 to 100 MB/s

4K - 4096 x 2680

Blackmagic RAW 3:1 - 135 MB/s

Blackmagic RAW 4:1 - 101 MB/s

Blackmagic RAW 5:1 - 81 MB/s

Blackmagic RAW 6:1 - 68 MB/s

Blackmagic RAW Q0 - 34 to 81 MB/s

Blackmagic RAW Q1 - 20 to 50 MB/s

Blackmagic RAW Q3 - 13 to 34 MB/s

Blackmagic RAW Q5 - 10 to 25 MB/s

Recording Formats

Blackmagic RAW 3:1, 8:1, 12:1, 18:1,

Q0, Q1, Q3 and Q5 at full sensor

width or height resolutions:

[12,288 x 8,040], [12,288 x 6,912],

[12,288 x 6,480], [12,288 x 5,112] and

[9,648 x 8,040]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 8:1, 12:1, 18:1,

Q0, Q1, Q3 and Q5 at Super 35

windowed sensor resolutions:

[9,408 x 6,264], [8,688 x 4,896],

[9,312 x 4,896], [9,312 x 3,864] and

[7,680 x 6,408]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 5:1, 8:1, 12:1,

Q0, Q1, Q3 and Q5 at full sensor

width or height scaled to:

[8,192 x 5,360], [8,192 x 4,608],

[8,192 x 4,320], [8,192 x 3,408] and

[6,432 x 5,360]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Blackmagic RAW 3:1, 4:1, 5:1, 6:1, Q0,

Q1, Q3 and Q5 at full sensor width or

height scaled to:

[4,096 x 2,680], [4,096 x 2,304],

[4,096 x 2,160], [4,096 x 1,704] and

[3,216 x 2,680]

with film, extended video or video

dynamic range or custom 3D LUT

embedded in metadata plus

simultaneous recording of H.264

1920 x 1080 Proxies.

Constant Quality Rates for 12K and 9K are: Q0 12:1 - 2.5:1, Q1 20:1 - 5:1, Q3 30:1 - 12:1, Q5 40:1 - 16:1

Constant Quality Rates for 8K and 4K are: Q0 12:1 - 5:1, Q1 20:1 - 8:1, Q3 30:1 - 12:1, Q5 40:1 - 16:1

Actual storage rates are dependent on image subject matter.

Software

Software Included

URSA Cine Blackmagic OS
DaVinci Resolve Studio for Mac and Windows including activation key
Blackmagic Camera Setup
Blackmagic RAW Player
Blackmagic RAW QuickLook Plugin
Blackmagic RAW SDK

Operating Systems



Mac 13.0 Ventura,
Mac 14.0 Sonoma or later.



Windows 10 and 11.

Power Requirements

Power Supply

+24V DC external power supply 100 -
240 AC 50/60Hz compatible with IEC
C14 socket.
Molex connector for rear
battery plate.

External Power Input

1 x 8 pin socket for external power or
battery use.
B-Mount battery plate.

Power Output

1 x 7-pin Lemo with +12V DC or +24V
DC power output depending on
camera supply.
1 x 3-pin Fischer with +12V DV or
+24V DC power output depending on
camera supply.
B-Mount battery plate with 2-pin
Lemo +12V regulated output
from camera.

Accessories

Optional Accessories

Blackmagic URSA Cine EVF
Blackmagic URSA Cine Mount PL
Blackmagic URSA Cine Mount LPL
Blackmagic URSA Cine Mount EF
Blackmagic URSA Cine Mount Shims
Blackmagic URSA Cine Battery Plate B Mnt
Blackmagic URSA Cine Battery Plate Gold
Blackmagic URSA Cine Battery Plate VLock
Blackmagic URSA Cine Baseplate 15
Blackmagic URSA Cine Baseplate 19
Blackmagic URSA Cine Handle
Blackmagic URSA Cine Grips
Blackmagic URSA Cine 5" LCD Sunshade
Blackmagic Media Dock
Blackmagic Media Module 8TB
Blackmagic Media Module CF
Blackmagic Video Assist 7" 12G HDR
Blackmagic Video Assist 5" 12G HDR
Blackmagic Video Assist 7" 3G
Blackmagic Video Assist 5" 3G
ATEM Streaming Bridge

Physical Specifications



Environmental Specifications

Operating Temperature
0° to 40°C (32° to 104°F)

Storage Temperature
-20° to 45°C (-4° to 113°F)

Relative Humidity
0% to 90% non-condensing

What's Included

Blackmagic URSA Cine 12K Body
Blackmagic URSA Cine Mount PL (installed)
Blackmagic URSA Cine Mount EF and screws
Blackmagic Media Module 8TB
URSA Cine Handle and bolts
URSA Cine Top Rod Mount 15
URSA Cine Baseplate 19
Plastic folding screen hood for 5" assist station
URSA Cine Battery Plate B Mount
WiFi Antennas
URSA Cine PL Body Cap
URSA Cine EF Body Cap
Rubber caps for connectors
+24V DC 250W power supply
DaVinci Resolve Studio with activation key
Welcome wallet with QR code for software download
Blackmagic Sticker
Custom foamed Pelican 1510 case

Warranty

12 Month Limited
Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2024, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller