

Key **Features**

- Integrated USB-C workstation offers audiovisual and data transfer, and power delivery up to 65W
- USB 3.2 hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort inputs for easy connectivity
- SuperClear® IPS panel with 100Hz variable refresh rate delivers fluid visuals
- Ergonomic tilt, swivel, pivot and height adjustment capabilities
- TCO, EnergyStar, EPEAT Silver certified for sustainability



Product **Description**

The ViewSonic VG2409-MHDU-2 is a 24" FHD monitor featuring USB 3.2 Hub with 1 upstream, 2 downstream ports, HDMI, and DisplayPort for business and home use. Simplify your work with just one cable that provides audiovisual, data and 65W power transfer. The 100hz variable refresh rate, Eye ProTech technology, and various ViewMode presets cater for optimal screen performance and comfortable viewing without tearing or stuttering. Expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low energy consumption.



- Menu Control Panel
 Power In
 VESA Compatible(Wall Mount 100 x 100 mm)
 HDMI
 HDMI
 USB Type-C

- 7. USB Type-B Upstream 8. USB Type-A Downstrea 9. Audio Out 10. Speakers

Visit Us

www.viewsonic.com



17:35	ViewSonic VG2409-MHDU-2 24" Full HD Ergor
DISPLAY	
Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,300:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	350 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG)): 4ms
Response Time (GTG w/OD):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	100
Variable Refresh Rate Technology:	Yes
Low Blue Light:	Software solution
Flicker-Free:	Yes
	NTSC: 72% size (Typ)
Color Gamut:	sRGB: 104% size (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)
COMPATIBILITY	
PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080
CONNECTOR USB 3.2 Type A Down Stream	: 2
	1
USB 3.2 Type B Up Stream: USB 3.2 Type C Up Stream;	1 (65W power charger)
DisplayPort Alt mode :	
3.5mm Audio Out:	1
HDMI 1.4:	1
DisplayPort:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
AUDIO	0.5W-W0
Internal Speakers:	2.5Watts x2
POWER	18W
Eco Mode (Conserve):	20W
Eco Mode (optimized):	
Consumption (typical):	22W
Consumption (max):	24W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	Internal Power Supply
ADDITIONAL HARDWARE	
Kensington Lock Slot:	1
Cable Organization:	Yes
CONTROLS Physical Controls:	Koy 1 (fovorito) Koy 2 Koy 2 Koy 4 Koy 5 (power)
Physical Controls: On Screen Display:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power) Input Select, Audio Adjust, ViewMode, Color Adjust,
	Manual Image Adjust, Setup Menu
OPERATING CONDITIONS	
Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%
WALL MOUNT	400 × 400
VESA Compatible:	100 x 100 mm
INPUT SIGNAL	20 a. 125KHz
Frequency Horizontal:	30 ~ 125KHz
Frequency Vertical:	48 ~ 100Hz
VIDEO INPUT	TMDS_HDMI (v4.4) POLE_Birdings + (v4.6) III
Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2), Micro- Packet - Type C

ERGONOMICS	
Height Adjust (mm):	130
Swivel:	360°
Tilt (Forward/Back):	-3.5° / 28°
Pivot (Right/Left):	90° / 90°
WEIGHT (IMPERIAL)	
Net (lbs):	12.3
Net Without Stand (lbs):	7.7
Gross (lbs):	15.9
WEIGHT (METRIC)	
Net (kg):	5.6
Net Without Stand (kg):	3.5
Gross (kg):	7.2
DIMENSIONS (IMPERIAL) (W	/XHXD)
Packaging (in.):	24.5 x 20.5 x 5.7
Physical (in.):	21.25 x 15.35~20.47 x 9.18
Physical Without Stand (in.):	21.25 x 12.72 x 2
DIMENSIONS (METRIC) (WX	HXD)
Packaging (mm):	622 x 520 x 144
Physical (mm):	539.7 x 389.89~519.89 x 233.29
Physical Without Stand (mm):	539.7 x 323.18 x 50.9
GENERAL	
Regulations:	Energy Star, EPEAT, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO
PACKAGE CONTENTS:	VG2409-MHDU-2 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market
Power Management:	Energy Star standards, EPEAT

