

## OVERVIEW

Upgradeable Outlet Level EC Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering a comprehensive view of outlet level power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. Upgrade the hot-swappable monitoring device on select units to leverage new technologies and accommodate changing business needs.

### Benefits

- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant
- Every unit is 100% tested for reliability and functionality. Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices.



## Part #: VP6G30A4

**Model Number:** MGR5MGB1-24PBB3-3PS56B2A10-S-A

**Category:** Monitored

**Sub Category:** Outlet Level

**Power Configuration:** 32A, 230/400V WYE, 22.0kW

**Physical Configuration:** 66in / 1683mm, Vertical

### Product Summary:

rPDU, Monitored Outlet Level EC, 32A, 230/400V WYE, 22.0kW, Vertical, (12) Locking IEC C13, (12) Locking IEC C19, 10ft / 3m power cord with 3P+N+E (IP44), Black Powder Coat.

### Monitoring:

Input and Outlet power monitoring. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display.

### Plug Form:



3P+N+E (IP44)

### Receptacle:



Locking IEC C13  
(Quantity: 12)



Locking IEC C19  
(Quantity: 12)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

## System Features

|                                           |                                                                                                                                                                                                    |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Monitoring                                | Input and Outlet power monitoring. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display. |
| Input Monitoring                          | Total Unit Monitoring (kWh, W, VA, PF)<br>Phase (A, B, C) Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements |
| Circuit Monitoring                        | Circuit / Breaker Monitoring (A)<br><br>Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy                                                                      |
| Outlet Monitoring                         | Outlet Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements.                                                   |
| Quantity Of Inputs                        | 1                                                                                                                                                                                                  |
| Voltage                                   | 200-240/346-415V WYE                                                                                                                                                                               |
| Current                                   | 32A x 3 Phase WYE                                                                                                                                                                                  |
| VA per Input (Load Capacity)              | 22.0kW (230V)                                                                                                                                                                                      |
| Frequency                                 | 50/60Hz                                                                                                                                                                                            |
| Over Current Protection                   | (6) 16A Single Pole Magnetic Breakers (10kAIC Rated)                                                                                                                                               |
| Switch                                    | Breaker/Switch Combination                                                                                                                                                                         |
| LCD Touchscreen Display / Auto Oriented   | Yes                                                                                                                                                                                                |
| Indicators - LED(s)                       | 24                                                                                                                                                                                                 |
| Power Cable Wire Gauge                    | 6mmÂ² H07RN-F                                                                                                                                                                                      |
| Power Cable Length                        | 10ft / 3m                                                                                                                                                                                          |
| Power Entry Location                      | Bottom Front                                                                                                                                                                                       |
| Plug Type                                 | IEC60309 3P + N + E, 32A, 230/400V, Splashproof IP44                                                                                                                                               |
| Combined Total Receptacle/Socket Quantity | 24                                                                                                                                                                                                 |
| Alternating Phase/Circuits                | Yes                                                                                                                                                                                                |
| Receptacle/Socket Type #1                 | U-Lock IEC C13                                                                                                                                                                                     |
| - Quantity on Face                        | 12                                                                                                                                                                                                 |
| - Quantity per Breaker                    | 2                                                                                                                                                                                                  |
| - Quantity per Phase                      | 6                                                                                                                                                                                                  |
| - U-Lock Color ID                         | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue                                                                                                                             |
| - Style                                   | Individual                                                                                                                                                                                         |
| - Voltage per Receptacle/Socket           | 230V                                                                                                                                                                                               |
| Receptacle/Socket Type #2                 | U-Lock IEC C19                                                                                                                                                                                     |
| - Quantity on Face                        | 12                                                                                                                                                                                                 |
| - Quantity per Breaker Pair               | 2                                                                                                                                                                                                  |
| - Quantity per Phase                      | 6                                                                                                                                                                                                  |
| - U-Lock Color ID                         | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue                                                                                                                             |
| - Style                                   | Individual                                                                                                                                                                                         |

|                                                              |                                                                                                                  |
|--------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| <b>- Voltage per Receptacle/Socket</b>                       | 230V                                                                                                             |
| <b>Network Connection</b>                                    | Dual 10/100/1000Mbps Ethernet                                                                                    |
| <b>Protocols Supported</b>                                   | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP |
| <b>Data Access Formats</b>                                   | CSV datalog, JSON API, JSON datalog                                                                              |
| <b>USB Support</b>                                           | Yes                                                                                                              |
| <b>IP Reset Button</b>                                       | Yes                                                                                                              |
| <b>Hard Reboot Button</b>                                    | Yes                                                                                                              |
| <b>Serial Connection</b>                                     | RS232 via RJ45                                                                                                   |
| <b>Remote Sensor RJ Connection Jacks</b>                     | 1 (Supports up to 16 Sensors)                                                                                    |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F                                                                                                       |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black                                                                                                            |
| <b>Configuration</b>                                         | Zero U                                                                                                           |
| <b>7938 Vertical Mounting Bracket Kit</b>                    | Yes                                                                                                              |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm                                                                          |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant                                                           |
| <b>Product Warranty</b>                                      | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years        |
| <b>Certification/Agency Approvals</b>                        | CE Marked                                                                                                        |
| <b>Certification/Agency Approvals</b>                        | UKCA Marked                                                                                                      |
| <b>Certification/Agency Approvals</b>                        | Complies with IEC 62368-1 (DOC Available)                                                                        |
| <b>Certification/Agency Approvals</b>                        | Complies with EN 55032 and EN 55035                                                                              |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant                                                                                                   |
| <b>Certification/Agency Approvals</b>                        | C <sub>e</sub> Mark                                                                                              |
| <b>Certification/Agency Approvals</b>                        | RCM Mark (EMC Only)                                                                                              |
| <b>Certification/Agency Approvals</b>                        | China RoHS                                                                                                       |
| <b>Chassis Dimensions (LxWxD)</b>                            | 66.25in x 2in x 2.6in / 1683mm x 51mm x 66mm                                                                     |
| <b>Shipped Weight</b>                                        | 22lbs (9.98kg)                                                                                                   |