



USB-C to HDMI 3-in-1 Docking Converter with Power Delivery

USB 3.2 Type-C Male to HDMI (4K@60Hz), USB-A (5 Gbps) and USB-C PD (100 W) Ports, Multiport Converter with Pass-through Charging Port, Aluminum, Space Gray

Part No.: [190299](#)

EAN-13: 0766623190299 | UPC: 766623190299

USB-C to HDMI Adapter 4K60 to connect a laptop, MacBook®, smartphone or tablet to an HDMI display - plus a USB-A peripheral and Power Delivery charging port

The Manhattan USB-C 3-in-1 HDMI Docking Converter with Power Delivery establishes a fast, simple and convenient link between a newer USB Type-C equipped media source (a laptop, PC, MacBook®, Chromebook™, computer, tablet, etc.) and existing HDMI display (monitor, TV or projector) for 4K at 60 Hz images in either mirror- or extended-display mode. Create a mini-workstation by adding any USB 3.2 Gen 1 (formerly USB 3.0) peripheral such as a mouse, keyboard, hub, external memory device and more with the integrated USB-A port. This multiport Docking Converter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your USB-C device. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Up to 100 W charging power input with USB-C Power Delivery (PD)

The included USB-C PD port lets you charge your notebook with output power up to 85 W while simultaneously charging your other mobile devices, such as smartphones or tablets, through the USB-A port. The Power Delivery function also provides faster charging than standard chargers since it determines the power needs of compatible devices and supplies it at the quickest and safest rate.

Take your phone to the big screen

If you have a smartphone or tablet that supports video output over USB-C DP Alt Mode, you can enjoy your apps and media even more. Watch a video on your monitor or flip through the slides of your presentation on a projector - all from your phone.

A multiport adapter that's made to go where you go

The very compact aluminum housing makes this USB-C to HDMI Converter the perfect travel companion. It's small enough to fit in an outer notebook bag pocket, so you can create a mini-workstation for your laptop where ever you're going.

Features:

- Easily connects a USB-C device to an HDMI display and USB-A peripheral while also charging both USB devices
- Resolutions up to Ultra-High-Definition (UHD) 4K@60Hz (3840×2160)
- One USB 3.2 Gen 1 Type-A port (formerly USB 3.0) with SuperSpeed transfer rates up to 5 Gbps and charging up to 5 W (5 V / 1 A)
- USB-A port to connect mice, keyboards or portable memory devices (and more) or to charge and sync a portable electronic device
- Supports USB Power Delivery (PD) function up to 85 W; requires an external PD charger - available from Manhattan
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple® MacBook®, Chromebook™, Pixel™ and more
- Sturdy, sleek aluminum housing, great for both desktop and travel
- Built-in, sturdy 11 cm (4 in.) cable with molded aluminum boot
- Lets your smartphone work like a desktop PC while also charging it (desktop setup requires devices with Android 9 or above that offer video output over USB-C)
- Plug-and-play installation; Windows®, macOS®, Chrome OS™, iPadOS® and Android™ compatible
- Compatible with USB4® and Thunderbolt™ 3 / 4 interfaces
- Fully HDCP 2.3 compliant, backward compatible
- Three-year warranty

Specifications:

Standards and Certifications

- DP 1.4 Alt Mode over USB-C
- USB 3.2 Gen 1
- HDMI 2.0

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- HDCP 2.3
- CE
- FCC
- RoHS
- REACH
- UKCA

General

- USB-A port data transfer speed: 5 Gbps
- Bus powered operation (except charging functions)
- USB-C PD charging port: 100.0 W (20.0 V at 5.0 A) max. input, 85.0 W output on USB-C connector
- USB-A charging: 5.0 W (5.0 V at 1.0 A) max.

Connections

- One USB-C 24-pin, male
- One USB-C 24-pin, female
- One USB-A 9-pin, female
- One HDMI 19-pin, female

Physical

- Dimensions (L x W x H): 70 x 29 x 12 mm (2.76 x 1.14 x 0.47 in.)
- Net weight: 30 g (1.06 oz.)
- Gross weight: 56 g (1.98 oz.)
- Cable length: 11 cm (4 in.)
- Cable diameter: 34 AWG
- Aluminum housing

Operating Environment

- Operation temperature: 0 - 45°C (32 - 113°F)
- Storage temperature: -10 - 70°C (14 - 158°F)
- Humidity (non-condensing): 5 - 90% RH

System Requirements

- Windows 7/8.1/10/11, Chrome OS, macOS, iPadOS or Android
- Note: Resolution on Chrome OS is limited to 4K@30Hz

Package Contents

- USB-C to HDMI 3-in-1 Docking Converter with Power Delivery
- Instructions

