

Delock External USB Type-C™ Dual Combo Enclosure for 2 x M.2 NVMe PCIe or SATA SSD - tool free

Description

This enclosure by Delock enables the installation of **two M.2 SSDs**. Either M.2 PCIe NVMe SSDs or M.2 SATA SSDs in 2280, 2260, 2242 and 2230 format can be used and operated. The **robust metal housing with cooling fins** ensures an optimum temperature of the memory.

Combo enclosure

The big advantage of this Delock M.2 enclosure is that both **SATA and PCIe (NVMe) M.2 SSDs** can be inserted into the enclosure. The memory is automatically recognized by the chipset and can then be used.

SSD installation without tools

The special feature of this enclosure is that **no tools** are required to install the M.2 SSD. The inner part can be pulled out by pushing the button, the SSD is inserted into the slot and attached to the board with a rubber nipple.



Item no. 42028

EAN: 4043619420285

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
external: 2 x USB 10 Gbps USB Type-C™ female
internal: 2 x M.2 key M slot
- Chipset: Realtek RTL9210B
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Bootable
- Data transfer rate up to 10 Gbps
- 2 x LED indicator for power and access
- Metal housing

- Dimensions (LxWxH): ca. 110 x 74 x 13 mm
- Hot Plug, Plug & Play

System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.2.3 or above
- Windows 10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 or Thunderbolt™ 4 port or
- A free USB Type-A port

Package content

- External enclosure M.2
- 2 x Cable USB-C™ male to USB-C™ male (with adapter to USB Type-A male), length ca. 45 cm
- 2 x thermal conductive pad
- 2 x thermal conductive plate
- 4 x rubber nipple
- User manual

Images



General

Function:	NVM Express (NVMe) Plug & Play
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Android 10.0 or above iPad Pro (3rd Generation) or above • iPad Air (2020) iPad Air (4th Generation) or above Mac OS 11.2.3 or above Windows 11 Linux Kernel 5.11 or above
Supported module:	M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on SATA or PCIe
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	2 x USB 10 Gbps USB Type-C™ female
Internal:	2 x M.2 key M slot

Technical characteristics

Chipset:	Realtek RTL9210B
Data transfer rate:	up to 10 Gbps

Physical characteristics

Housing material:	Aluminium
Cable length:	45 cm
Length:	110 mm
Width:	74 mm

Height:	13 mm
Colour:	grey