



Active holder with USB-cable and cig-plug adapter

With USB-A cable + cig-plug adapter with 2 USB-A ports: QC 3.0A + 2.4A. With tilt swivel. 12/24 Volt. For devices with original Boot/skin (CT30P-PB-XP).

Item no: 721335

EAN Number: 7320287213355

Keep your units battery fully charged in an active holder, always within easy sight and reach! Neat, discreet and convenient. Custom made with a perfect, firm fit. With USB-A cable with cig-plug adapter, choose to connect either to the vehicle's USB-A outlet or the 12/24V socket. The cig-plug adapter has two USB-A ports: QC 3.0A + 2.4A. You have full access to the camera and all buttons when the device is in the holder. It is easy to slide the device into place in the holder so it connects to the charging, and to take it out of the holder when leaving the car.

The holder is equipped with a tilt swivel so you can easily adjust the angle for better viewing, or switch between portrait and landscape mode. Tilts 17° and swivels 360°. Mounting plate 42x50 mm with 4 mm AMPS-holes. Made of high grade black ABS/Acetal plastic. Made in Sweden. Attach onto a ProClip Mounting Platform or a Pedestal Mount.

Fits the following models:

Honeywell CT30XP

For a complete list, see

www.brodit.com/en/product/721335

Measurements:

Height 104 mm

Width 88 mm

Depth 58 mm

Volume 531 cm³

Weight 176 g

Charging specifications:

- Output Connector Type: Dual USB Type-A Female.
- Output Voltage: 5V, 9V, 12V(Nominal)
- Output Current:
- USB Port 1: 4.9V ~ 5.25V 2.4A (White port, recommended for Apple)
- USB Port 2: QC3.0. 3.6V ~ 6V/3A 6.2-9V/2A 9.2-12V/1.5A (Green port, recommended for Android etc)
- Output Voltage Ripple: 300mV pk-pk at Max Load
- Input Voltage Range: DC 12--24V DC, Input can handle 40V Load dump transient events
- Input Current: 3.0 A DC Max
- Input Current with No device attached: 0.005A
- DC-DC Conversion Efficiency: Over 86% Typical
- Rated Power:
- USB Port 1: 12 Watts Max. White port.
- USB Port 2: 18 Watts Max. Green port.