

## ENGAGE 75 SE

# Engineered to be the world's most powerful professional wireless headsets.

- > Industry-leading wireless performance. Better customer connections.
- > More talk time, less interruptions. Increase productivity.
- > Crystal-clear calls. Enhance the customer experience.



Product name		Engage 75 SE Stereo	Engage 75 SE Mono	Engage 75 SE Convertible
<b>General info</b>	<b>Box contents</b>	Headset, Phone adapter cable, user documents, Headset base unit, Mounting bracket, power supply, USB-C to USB-A cable	Headset, Phone adapter cable, user documents, Headset base unit, Mounting bracket, power supply, USB-C to USB-A cable	Headset, 3 sets of EarGels™, Ear hook, Head band, Phone adapter cable, Neckband, user documents, Headset base unit, power supply, USB-C to USB-A cable
	<b>Packaging dimensions (WxHxD)</b>	190mm x 93mm x 147mm   7.48in x 3.66in x 5.79in	190mm x 93mm x 147mm   7.48in x 3.66in x 5.79in	145mm x 93mm x 190mm   5.7in x 3.66in x 7.48in
	<b>Headset Weight</b>	90g   3.17oz	64g   2.26oz	21g   0.74oz
	<b>Warranty</b>	2 years	2 years	
	<b>LED features and functions</b>	Answer/end call, Battery status, Busylight, deskstand docking indication, Firmware update status, incoming call, Mute/unmute, Power indicator, Volume up/down	Answer/end call, Battery status, Busylight, deskstand docking indication, Firmware update status, incoming call, Mute/unmute, Power indicator, Volume up/down	Answer/end call, Battery status, Busylight, deskstand docking indication, Firmware update status, incoming call, Mute/unmute, Power indicator, Volume up/down
	<b>Certifications and compliance</b>	Zoom, Works with all leading UC platforms, Google Meet, Amazon Chime, Works With Chromebook, Microsoft Open Office certification	Zoom, Works with all leading UC platforms, Google Meet, Amazon Chime, Works With Chromebook, Microsoft Open Office certification	Zoom, Works with all leading UC platforms, Google Meet, Amazon Chime, Works With Chromebook
<b>Audio</b>	<b>Speaker size</b>	28mm	28mm	13mm
	<b>Speaker frequency range</b>	40Hz - 16000Hz	40Hz - 16000Hz	40Hz - 16000Hz
	<b>Speaker bandwidth (music mode)</b>	40Hz - 16000Hz	40Hz - 16000Hz	40Hz - 16000Hz
	<b>Speaker bandwidth (speak mode)</b>	150Hz - 6800Hz	150Hz - 6800Hz	150Hz - 6800Hz
	<b>Microphone type</b>	1 Analog MEMS and 1 Analog ECM	1 Analog MEMS and 1 Analog ECM	Electret Condenser (ECM) Uni-Directional Microphone
	<b>Microphone bandwidth</b>	100Hz - 10000Hz	100Hz - 10000Hz	100Hz - 10000Hz
<b>Software &amp; Apps</b>	<b>Compatible software and/or apps</b>	Jabra Direct, Jabra SDK, Jabra Xpress	Jabra Direct, Jabra SDK, Jabra Xpress	Jabra Direct, Jabra SDK, Jabra Xpress
<b>Fit &amp; Comfort</b>	<b>Form factor</b>	On-ear headband	On-ear headband	Mono, behind-the-ear, On-ear headband
<b>Battery</b>	<b>Talk time</b>	Up to 13 hours (with busylight off)	Up to 13 hours (with busylight off)	Up to 9 hours (with busylight off)
	<b>Corded charging</b>	USB-C™	USB-C™	USB-C™
	<b>Sleep mode</b>	Yes	Yes	Yes
	<b>Charging time</b>	Up to 90 minutes	Up to 90 minutes	Up to 90 minutes
	<b>Battery status % after 30 min / 60 min</b>	40% after 30 min charging and 80% after 60 min charging	40% after 30 min charging and 80% after 60 min charging	40% after 30 min charging and 80% after 60 min charging
	<b>Battery type</b>	Rechargeable lithium-ion battery	Rechargeable lithium-ion battery	Rechargeable lithium-ion battery
	<b>User exchangeable battery</b>	Yes	Yes	

<b>Connectivity</b>	<b>Wireless technology</b>	Bluetooth, DECT	Bluetooth, DECT	Bluetooth, DECT
	<b>Bluetooth® version</b>	5.0	5.0	5.0
	<b>Bluetooth® Multipoint</b>	Yes	Yes	Yes
	<b>Operating range</b>	Up to 150m   490ft	Up to 150m   490ft	Up to 100m   330ft
	<b>Paired devices</b>	Up to 2 Bluetooth® devices	Up to 2 Bluetooth® devices	Up to 2 Bluetooth® devices
<b>Extended info</b>	<b>Power consumption</b>	Up to 0.65A / 7.5V / 4.875W	Up to 0.65A / 7.5V / 4.875W	Up to 0.65A / 7.5V / 4.875W
	<b>Operating temperature</b>	-10°C to 55°C   14°F to 131°F	-10°C to 55°C   14°F to 131°F	-10°C to 55°C   14°F to 131°F
	<b>Storage temperature</b>	-5°C to 45°C   23°F to 113°F	-5°C to 45°C   23°F to 113°F	-5°C to 45°C   23°F to 113°F

PRODUCT TYPE	SKU	DESCRIPTION
--------------	-----	-------------

<b>Products</b>	9655-583-125	Jabra Engage 75 SE - Convertible
	9656-583-125	Jabra Engage 75 SE - Mono
	9659-583-125	Jabra Engage 75 SE - Stereo
<b>Accessories</b>	14101-60	Jabra Engage Ear Cushions – 5 pairs for Stereo headset
	14101-61	Jabra Engage Ear Cushions – 10 pieces for Mono headset
	14101-72	Jabra Engage Ear Cushions – 1 pair for Stereo headset
	14101-73	Jabra Engage Ear Cushions – 2 pieces for Mono
	14121-34	Jabra Engage Headband Pad - Black, 5 pieces
	14121-37	Jabra Engage Mono Neckband
	14121-38	Jabra Engage Neckband for Convertible headset
	14121-39	Jabra Engage Mono Headband
	14121-40	Jabra Engage Headband for Convertible headset
	14121-41	Jabra Engage Convertible EarGels and Earhook Pack
	14201-12	Standard RJ9 to RJ9 Flat Cord with Modular Plug (857 mm)
	14205-13	Jabra Link 400a USB-A, DECT, UC, NA
	14205-23	Jabra Link 400a USB-A, DECT, MS, NA
	14205-33	Jabra Link 400c USB-C, DECT, UC, NA
	14205-43	Jabra Link 400c USB-C, DECT, MS, NA
	14207-42	Jabra Engage Power Supply - EMEA
	14207-43	Jabra Engage Power Supply - NA
	14207-44	Jabra Engage Power Supply - APAC (UK/AU/NZ)
	14208-31	Jabra USB-A to USB-C cable - Black
	14208-32	Jabra USB-C to USB-C cable - Black
	14217-01	Jabra Engage SE Desk Stand (Stereo/Mono), USB-A
	14217-02	Jabra Engage SE Desk Stand (Convertible), USB-A
	14217-05	Jabra Engage SE Desk Stand (Stereo/Mono), USB-C
	14217-06	Jabra Engage SE Desk Stand (Convertible), USB-C
	14401-42	Jabra Engage SE Replacement Headset - Mono
	14401-47	Jabra Engage SE Replacement Headset - Stereo
	14401-52	Jabra Engage SE Replacement Headset - Convertible

Please note that different regions use different DECT frequencies. Therefore it is important to select the appropriate SKU for the region where the headset will be used.

#### Jabra Engage 75 SE Tech Sheet 06082024

Download the latest version of this document at:  
[jabra.com/support](https://jabra.com/support)