




HIGH CURRENT GAMER

HCG850 PRO Platinum ATX 3.1

FOR THE ULTIMATE GAMER

Presenting our High Current Gamer PRO Platinum ATX3.1 power supplies, designed with the ultimate quality and stability in mind for gamers and enthusiasts. With the ground-breaking features like ATX 3.1, PCIe 5.1, 100% high-quality JP capacitors, 80 PLUS® Platinum-certified efficiencies and other more, you can expect second-to-none performance from your system. The PhaseWave™ Design ensures steady power output, while the 135mm FDB Silence Fan offers quiet cooling. The power supply is also 100% Modular, allowing for easy cable management and customization. The Zero RPM Manager enables advanced thermal control, ensuring the optimal balance between silent operation and efficient cooling. The CircuitShield™ full suite of industrial-grade protections provides safe and reliable power delivery under any circumstances. HCG850 PRO Platinum ATX3.1 is the perfect choice for your cutting-edge PC system.



ATX 3.1 & PCIe 5.1 COMPATIBLE

Our new HCG PRO Platinum ATX3.1 power supplies are formally certified for ATX 3.1 compliance, meeting the high standards for reliability and power efficiency, and ensuring the utmost level of quality and performance.


The included PCIe 5.1 12VHPWR GPU cable enables seamless compatibility with the latest graphics cards, such as the NVIDIA® GeForce RTX™ 40 Series.

RELIABILITY




100% HIGH-QUALITY JP CAPACITORS

Equipped with 100% high-quality JP capacitors, HCG PRO Platinum ATX3.1 achieves unprecedented tight voltage regulation and minimal ripple and noise, maximizing your system's performance.



PHASEWAVE™ DESIGN

Introducing our PhaseWave™ Design, with server-class full-bridge LLC design featuring synchronous rectification based on a DC-DC topology, ensuring unparalleled power delivery efficiency and stability for your gigs.



CIRCUITSHIELD™




The full suite of industrial-grade protections includes OCP, OVP, UVP, SCP, OPP, OTP, SIP, and NLO, providing the best dependability for your power supply in any situation.



10-YEAR WARRANTY

Pushing the standard for excellence with the full-suite industrial protections, backed by a 10-year warranty duly committed by Antec.

FAN FUNCTION




ZERO RPM MANAGER

The thermal sensors activate the fan only when necessary, providing optimal cooling while minimizing noise levels. With the Zero RPM fan mode, our PSU comes with a longer lifespan and quieter operation.




135MM FDB SILENT FAN

The whisper-quiet 135mm fluid-dynamic bearing (FDB) fan delivers high airflow with the durability and longevity that is a signature of Antec quality.



SYSTEM BUILD & CABLE MANAGEMENT



FULL MODULAR CABLE MANAGEMENT

Allowing users to use only the necessary cables and eliminates excess cables that can obstruct and reduce airflow, also provide a much cleaner look inside the PC case.



CABLES

QTY	Cable Length	Cable Type	Connector(s) Per Cable
1	610 mm	24(20+4)pin M/B	1
1	750 mm	16(12+4)pin PCIe 5.1 12VHPWR (600W)	1
2	700 mm	8(4+4)pin CPU	1
3	750 mm	8(6+2)pin PCI-E	1
3	500 mm, 150 mm, 150 mm, 150 mm	SATA	4
1	400 mm, 150 mm	SATA	2
1	450 mm, 100 mm, 100 mm	Molex	3

CONNECTORS

x1	x1	x2	x3	x14	x3

INPUT

100-240V~, 50Hz-60Hz, 11A-5.5A / 200-240V~, 50Hz-60Hz, 5.5A for China and Korea

OUTPUT

+3.3V	+5V	+12V	-12V	+5VSB
20A	20A	70A	0.3A	3.0A
100W		840W	3.6W	15W
850W				

SPECIFICATIONS

Model	HCG850 PRO Platinum ATX3.1
Type	ATX 12V 3.1
Dimension	160(L)*150(W)*86(H)
Modular	Full-Modular
Warranty	10 years
Input Voltage	100V-240V
Input Current	11A-5.5A
Input Frequency Range	60Hz-50Hz
PFC	Active PFC
Power Good Signal	100-150ms
Protection	OCP, OVP, UVP, SCP, OPP, OTP, SIP, NLO
Output Capacity	850W
Operation Temperature	0-40°C
Regulatory	cTUVus/TUV/CB/RCM/CE/FCC/BIS/BSMI/KC/UKCA/ICES/CCC
Fan	135mm FDB Silent Fan
Certifications	80 Plus Platinum
Connector	1 x 24(20+4)pin MB 1 x 16(12+4)pin PCIe 5.1 12VHPWR 2 x 8(4+4)pin CPU 3 x 8(6+2)pin PCI-E 14 x SATA 3 x Molex
Unit Box Dimensions	336(L)*198(W)*133(H)
Net Weight	3.39kg
Gross Weight	3.86kg
UPC#	0-761345-20006-6 HCG850 PRO P JS 0-761345-20007-3 HCG850 PRO P JP 0-761345-20008-0 HCG850 PRO P GB 0-761345-20009-7 HCG850 PRO P EC 0-761345-20010-3 HCG850 PRO P AU 0-761345-20011-0 HCG850 PRO P CN