


MPN: LVO231205-FLEX

Bendable LC-LC Multimode fibre cable duplex 5m OM3 LSZH

The Lanview Bendable series is engineered for flexible cable management, able to bend and sustain any angle from a straight line to 90 degrees. The boot, shaped around a single stainless-steel wire, is easily adjustable by hand, while the internal wire maintains the set angle or direction.

The boot's design permits repositioning at any moment or straightening for the disconnection of connectors. Its versatility guarantees ideal connector positioning in demanding situations, like confined areas or environments with high density.

- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- Color: Aqua
- Bending radius: 30 mm
- LC/UPC Connector
- Cable Diameter 2.0mm
- Fibre Standard G.652.D



Specifications

Features		
Cable length	5 m	
Cable type	Duplex	
Cladding diameter	125 µm	
Compressive strength	10	
Connector 1	LC/UPC	
Connector 1 gender	Male	
Connector 2	LC/UPC	
Connector 2 gender	Male	
Connector gender	Male/Male	
Connector polish type	UPC	
Core diameter	50 µm	
Fiber mode structure	Multi-mode	
Fibre optic type	OM3	
Full duplex	Yes	
Halogen-free	Yes	
Insertion loss	0.3 dB	
Jacket material	Low smoke zero halogen (LSZH)	
Plug and Play	Yes	
Product colour	Aqua colour	
REACH compliance	Yes	
Return loss	35 dB	
RoHS compliance	Yes	
Wavelengths supported	850, 953, 1260, 1280, 1300 nm	

Operational conditions	Operating temperature (T-T)	-40 - +75 °C
	Storage temperature (T-T)	-40 - +85 °C
Other features	Core / cladding diameter	50/125 µm
Technical details	Doesn't contain	Halogen
Vendor information	Brand Name	Lanview
	Warranty	25 Year(s)
Weight & dimensions	Bending radius	3 cm
	Cable diameter	2 mm

Other products in this series

Cable length	
0.5	LVO2314705-FLEX
1	LVO231469-FLEX
2	LVO231301-FLEX
3	LVO231203-FLEX
5	LVO231205-FLEX
7.5	LVO2312075-FLEX
10	LVO231472-FLEX
15	LVO231215-FLEX
20	LVO231220-FLEX
25	LVO231225-FLEX
30	LVO231230-FLEX

Other images

