



1m USB 2.0 Type C Cable, 2 x 90° Right Angle

No.: 32009

USB Type C Male to Male

Description

- Entry level USB 2.0 Type C cable for home and small office applications
- Both USB Type C plugs are angled at 90°
- Supports data rates of up to 480Mbit/s
- Robust PVC housing with nickel-plated contacts
- 10 year warranty

LINDY USB 2.0 Type C cables feature double shielded construction with copper conductors for premium performance and corrosion resistance. Nickel connectors and gold plated contacts maintain signal integrity and reliability.

Data transfer speeds up to 480Mbps are supported for the quick and effortless transfer of large data volumes.

USB Type C features a reversible connector, so no matter which orientation the cable is inserted, a connection will always be found. This connector allows a fully bi-directional cable with automatic host and device negotiation.

USB 2.0 Type C, 2 x 90° Right Angle cables are available in the following lengths: 0.5m, 1m.

Technical details

Connectors

- Connector A: USB 2.0 Type C Male 90° Right Angle
- Connector B: USB 2.0 Type C Male 90° Right Angle
- Housing Material: PVC
- Shielding in head shell: -
- Connector Plating: Nickel
- Pin Construction: Copper
- Pin Plating: Gold
- Dimensions [approx.] WxDxH: 7.5x27x15mm [0.3x1.06x0.59in]

Cable Construction

- Length: [3.28ft]
- Standard: USB 2.0
- Power Delivery: -
- Max. Power: 60W
- Colour: Black
- Type: Round
- Jacket Diameter: 3.8mm [0.15in]
- Jacket Material: PVC

Conductor Material: Copper
Conductor Gauge Power: 22 AWG
Conductor Gauge Data: 28 AWG
Shielding: Aluminium Foil 110%

Specifications

Supported Bandwidth: 480Mbps
Nominal Attenuation: 0.5Mhz- 400Mhz < 5.8db
Minimum Bend Radius: 38mm (1.5in)
Operating Temperature: 0°C - 40°C (32°F - 104°F)
Storage Temperature: 0°C - 70°C (32°F - 158°F)

Miscellaneous

Packaging Type: Polybag
Warranty (Years): 10
Product Compliance: RoHS, REACH, California Proposition 65

Purchasing Information

No.: 32009
EAN: 4002888320092

This product is also available in other lengths

32008 - 0.5m (1.64ft)
32009 - 1m (3.28ft)