

Delock USB 40 Gbps Enclosure for 1 x M.2 NVMe SSD in Gaming Style with LED and Fan - tool free

Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280 format, it can be connected via Thunderbolt™ 3, Thunderbolt™ 4 or **USB-C™** to the PC or laptop.

USB 40 Gbps

Due to **USB 40 Gbps** compatibility, the Delock enclosure can be connected to Thunderbolt™ 3 and 4 ports, as well as to all USB Type-C™ ports. The maximum data transfer rate depends on the host device.

LED illumination

In addition to the Power LED there is an **LED light bar** on the side. This glows in pulsating blue light when the enclosure is connected to a USB interface and in colourful illumination when connected to a Thunderbolt™ interface.

SSD installation without tools

The special feature of this enclosure is that **no tools are required** to install the M.2 SSD.

Active cooling by fan

A **silent fan** in the bottom area of the enclosure ensures **sufficient cooling** of the used SSDs, so that the operation also works without problems with the enclosure closed. The fan can be switched on and off.

Note

Due to the USB to NVMe controller, the data transfer rate on a USB Gen 2x2 port is only 10 Gbps.



Item no. 42025

EAN: 4043619420254

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
external: 1 x USB 40 Gbps USB Type-C™ female

internal: 1 x M.2 key M slot

- Chipset: Intel JHL7440, Realtek RTL9210B
- Supports M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 40 Gbps
- 1 x LED indicator for power
- LED light bar indicates whether connected by USB or Thunderbolt™ port
- On / off button for enclosure and fan
- Metal housing
- Built-in 30 mm fan
- Hot Plug, Plug & Play
- Dimensions (LxWxH): ca. 117 x 56 x 16 mm


System requirements

- Android 10.0 or above
- Chrome OS 90.0 or above
- iPad Air (4th Generation) or above
- Linux Kernel 5.13 or above
- Mac OS 12.4 or above
- Windows 10/10-64/11
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port or
- Device with a free Thunderbolt™ 4 port

Package content

- External enclosure M.2
- Thunderbolt™ 4 cable, length ca. 50 cm
- 1 x thermal conductive pad
- 2 x rubber nipple
- User manual

Images



General

Function:	Plug & Play
Supported operating system:	Windows 10 32-Bit Windows 10 64-Bit Android 10.0 or above iPad Air (4th Generation) or above Chrome OS 90.0 or above Windows 11 Mac OS 12.4 oder höher Linux Kernel 5.13 or above
Supported module:	Supports M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe)
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x USB 40 Gbps USB Type-C™ female
Internal:	1 x M.2 key M slot

Technical characteristics

Data transfer rate:	40 Gbps
---------------------	---------

Physical characteristics

Housing material:	Aluminium
Length:	117 mm
Width:	56 mm
Height:	16 mm
Colour:	silver

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin

Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de