


Delock Cable Optical Fibre LC-APC to SC-APC Simplex Singlemode OS2 3 m

Description

This fibre optic cable by Delock can be used to connect various network devices, e.g. an FTTH house interconnection point with a fibre optic modem.



3 m

Item no. 83862

EAN: 4043619838622

Country of origin: China

Package: Zip poly bag

Technical details

- Connectors:
 - 1 x LC-APC Simplex
 - 1 x SC-APC Simplex
- APC 8°
- Ceramic ferrule with dust protection
- Singlemode OS2 cable G657.A2
- Fibre: 9/125 µm
- Insertion loss < 0.15 dB
- Return loss > 60 dB
- Smallest bending radius: 7.5 mm
- Cable diameter: ca. 2.0 mm
- LS0H (halogen-free)
- Operating temperature: -20 °C ~ 70 °C
- Colour: yellow
- Cable length: ca. 3 m

Package content

- Optical fiber cable

Images



General

Specification:	OS2
----------------	-----

Interface

Connector 1:	1 x LC Simplex male
Connector 2:	1 x SC Simplex male

Technical characteristics

Operating temperature:	-20 °C ~ 70 °C
------------------------	----------------

Physical characteristics

Cable colour:	yellow
Cable length incl. connector:	0.5 m
Smallest bending radius:	7.5 mm
Cable jacket material:	LS0H (halogen-free)