

Delock M12 Cable L-coded 5 pin male to female PUR suitable for drag chains 1 m grey

Description

This M12 sensor cable by Delock can be used for direct current applications. The L-coded version has 5 power contacts with a rated current of 16 A at 63 V with which currents can be reliably transmitted. This can be used to supply power to fieldbus components, power supply units, industrial machines and motors, for e.g., where a high current and low voltage are required.



1 m

Item no. 80537

EAN: 4043619805372

Country of origin: China

Package: Zip poly bag

Technical details


- Connectors:
 - 1 x M12 male 5 pin L-coded
 - 1 x M12 female 5 pin L-coded
- Copper conductor
- Shielded
- Cable gauge: 14 AWG (2.5 mm²)
- Rated current: 16 A / 63 V
- Spanner width: SW13
- Cable diameter: ca. 10.4 mm
- Cable jacket material: PUR
- Suitable for drag chains
- Drag chain speed: up to max. 5 m/s
- Tightening torque: 0.6 Nm
- Bending radius (fixed): 5 x outer diameter
- Bending radius (movable): 10 x outer diameter
- Max. number of bending cycles: 5,000,000
- Max. number of torsion cycles: 500,000
- Torsional stress: ± 180 °/m
- Operating temperature (fixed): -40 °C ~ 80 °C

- Operating temperature (movable): -25 °C ~ 75 °C
- Flammability class: UL94HB
- Halogen-free, silicone-free, oil-resistant
- Protection class: IP66 / IP67
- Material thread: zinc diecast
- Colour: grey
- Length incl. connectors: ca. 1 m

Package content

- M12 cable

Images



General

Protection category:	IP66 / 67
----------------------	-----------

Interface

Connector 1:	1 x M12 male 5 pin L-coded
Connector 2:	1 x M12 female 5 pin L-coded

Physical characteristics

Conductor material:	copper
Conductor gauge:	14 AWG (2.5 mm ²)
Material:	PUR
Shielding:	unshielded
Length:	1 m
Colour:	grey
Spanner width:	7.2 mm
Cable diameter:	10.4 mm
Safety of Flammability:	UL94HB