

# Delock Push Button for Installation 19 mm 4 x Screw Terminal LED yellow

## Description

This push button by Delock is ideal for **installation in control panels**, for example in **industry, control or regulation technology**. Push buttons can also be found in the **automotive industry** or the consumer sector. For example, as doorbells or triggers for lighting systems with timers such as those found in hallways.



## Button

A so called button, or push button, returns to its initial position after being pressed.

**Item no. 20979**

EAN: 4043619209798

Country of origin: China

Package: Retail Box

## Opener and closer

The NO (closer) contact establishes a connection between two contacts, while the NC (opener) contact releases them.

## Note

- The installation should only be carried out by qualified electricians in compliance with the usual national power supply guidelines.
- Earthing is necessary for low-voltage systems to ensure the safety and functionality of the system.

## Technical details

- Connectors: 4 x screw terminal
- Switch type: 1NO +1NC
- Switching voltage: AC 230 V~ / 3 A
- Number of contacts: 4
- Number of open contact: 1
- Function: momentary
- Actuator: flat
- Operating temperature: -25 °C ~ 55 °C
- Mounting hole diameter: ca. 19 mm
- Hexagon nut spanner width: 22 mm

- Mounting depth: ca. 28 mm
- Thread size: M19
- LED lighting: yellow
- LED voltage: 12 V
- LED type: ring
- Material: stainless steel nickel plated
- Mechanical life: 1,000,000 cycles
- Electrical service life: 100,000 cycles
- Protection class: IP65
- Dimensions (LxD): ca. 30 x 25 mm


---

## Package content

- Push-button

---

## Images



## General

|                      |                |
|----------------------|----------------|
| Mounting type:       | Screw mounting |
| Protection category: | IP65           |
| LED indicator:       | ring           |
| Style:               | momentary      |

## Technical characteristics

|                        |                |
|------------------------|----------------|
| Operating temperature: | -25 °C ~ 55 °C |
|------------------------|----------------|

## Physical characteristics

|                         |                               |
|-------------------------|-------------------------------|
| Housing material:       | stainless steel nickel plated |
| Colour:                 | silver                        |
| Thread type:            | M19                           |
| LED colour:             | yellow                        |
| Mounting hole diameter: | 19 mm                         |