

# TAA-COMPLIANT CAT6A BULK CABLE

1000ft (304.8m) TAA-Compliant Cat6a Bulk Foil Shield (F/UTP) Ethernet Network Cable with Solid Conductors – Riser CMR-Rated

C2G's TAA-Compliant Cat6a Bulk Cable is an excellent choice for customized horizontal network installations. It supports data frequency range up to 660 MHz. Featuring an integrated metal foil screen with a drain wire, this cable significantly reduces electromagnetic interference (EMI) and crosstalk, ensuring superior signal transmission and minimizing data errors. The new sustainable slim packaging reduces plastic and cardboard waste by 40%. The packaging takes up less space and also provides a smooth cable pulling experience.



**\*TAA  
COMPLIANT**

## FEATURES

- Supports data frequency range up to 660 MHz
- Riser, CMR-Rated jacket
- Overall metal foil screen with drain wire for enhanced network performance, reliability, and safety
- Solid bare copper construction for high-quality signal transmission
- Meets or exceeds Cat6a cabling standards, including ANSI/TIA-568.2-D
- Innovative, sustainable packaging with space-saving design and seamless cable pulling experience



## ITEM

## DESCRIPTION

C2G56050 1000ft (304.8m) TAA-Compliant Cat6a Bulk Foil Shield (F/UTP) Ethernet Network Cable with Solid Conductors – Riser CMR-Rated - Blue

# TAA-COMPLIANT CAT6A BULK CABLE

1000ft (304.8m) TAA-Compliant Cat6a Bulk Foil Shield (F/UTP) Ethernet Network Cable with Solid Conductors – Riser CMR-Rated


## SPECIFICATIONS

		C2G56050	
PHYSICAL SPECIFICATIONS	Conductor	Material	23AWG solid bare copper Polyolefin (PO)
	Insulation	Color code and diameter	Blue & white/blue stripe: 1.11 ± 0.02 mm Orange & white/orange stripe: 1.06 ± 0.02 mm Green & white/green stripe: 1.11 ± 0.02 mm Brown & white/brown stripe: 1.05 ± 0.02 mm
	Jacket	Material Diameter Thickness Color	Flame retardant polyvinyl chloride (FRPVC) 7.4 ± 0.2 mm 0.55 ± 0.05 mm Blue
	Filler	Material	Polyolefin (PO)
	Shield	Material	Mylar tape
		Description	100% coverage and mylar side facing out
	Drain wire	Material	26AWG solid tinned copper
	Overall cable	Outer Box Dimension	L1.53 x W0.87 x H1.6 ft L465 x W265 x H475 mm
		Weight	37.9lb (17.12 kg)
	Storage Temperature	-4°F to 167°F (-20°C to 75°C)	
	Operation Temperature	-4°F to 167°F (-20°C to 75°C)	
	Minimum bending radius	≥ 8 times of overall diameter	
	Maximum pulling tension	≤ 110 N	
ELECTRICAL SPECIFICATIONS	Voltage	300V	
	Spark test	2.5 KV DC	
	AC leakage current through overall jacket	≤ 10mA (1.5KV AC)	
	Cable cold bend test	-20°C for 4 hr	
	Conductor DC resistance	≤ 9.38 Ω/100m	
	Resistance unbalance	≤ 4%	
	Dielectric strength	1.5 KV ac for 2 s	
	Insulation resistance	≥ 5000 MΩ·km	
	Mutual capacitance	≤ 5.6 nF/100m	
	Capacitance unbalance pair-to-ground	≤ 330 pF/100m	
	Nominal Velocity of Propagation	68%	
	Propagation Delay	570ns/100m (maximum)	
	Delay Skew	45ns/100m (maximum)	
APPLICABLE STANDARD	Electrical Transmission	ANSI/TIA-568.2-D (2018); ISO/IEC 11801-1; IEC 61156-5 (Edition 2.1)	
	Flame Test	UL 1666 (CMR)	
	Material and Construction	UL 444; LP-Rating 0.5A; CSA 22.2 NO.214	
	EU Directive	2011/65/EU & 2015/863/EU; 2006/95/EC (LVD)	

# TAA-COMPLIANT CAT6A BULK CABLE

1000ft (304.8m) TAA-Compliant Cat6a Bulk Foil Shield (F/UTP) Ethernet Network Cable with Solid Conductors – Riser CMR-Rated

## TECHNICAL DRAWING



LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

### SIMPLIFIED CONNECTIVITY

USA 800.506.9607 customer-service@c2g.com

APAC +852 2145 4099 av.asia.sales@legrand.com

EMEA +31 495 580 840 c2g.emea@av.legrand.com

©2024 Legrand AV Inc. 240497 Rev A 8/24 C2G is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.