

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration.
- Standard 1 year warranty.



## Part #: EPOG90A0

**Model Number:** VC0ABE2A20B4DXX

**Category:** Basic

**Subcategory:** Standard

**Power Configuration:** 32A, 230V, 7.3kW

**Physical Configuration:** 59in / 1500mm, Vertical

**Product Summary:** rPDU - Basic Standard, 32A, 230V, 7.3kW, Vertical, (20) Manual Lock IEC C13, (4) Manual Lock IEC C19, 3m power cord with 2P+E (IP44), Black Powder Coat

### Plug Form:



1P+N + E

### Receptacle:



Manual Lock IEC C13  
(Quantity: 20)



Manual Lock IEC C19  
(Quantity: 4)

### Chassis Color



## Vertiv.com

© 2024 Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

## Product Specification and Options

### System Features

Quantity Of Inputs	1
Voltage	230V
Current	32A
VA per Input (Load Capacity)	7.3kW
Frequency	50/60Hz
Over Current Protection	(2) 16A Single Pole Magnetic Breakers
Switch	Breaker/Switch Combination
Power Cable Wire Gauge	4mm <sup>2</sup> H07RN-F
Power Cable Length	10ft / 3m
Input Type	IEC60309 2P + E, 32A, 250V, Splash proof IP44
Receptacle/Socket Type #1	Manual Lock IEC C13
- Quantity	20
- Quantity per Breaker	10
- Manual Lock Color	Black
- Maximum Output per Receptacle/Socket	10A
- Voltage per Receptacle/Socket	230V
Receptacle/Socket Type #2	Manual Lock IEC C19
- Quantity	4
- Quantity per Breaker	2
- Manual Lock Color	Black
- Maximum Output per Receptacle/Socket	16A
- Voltage per Receptacle/Socket	230V
Maximum Operating Temperature	45°C/113F
Heavy Steel - Powder Coat Finish	Black
Configuration	0U, Vertical
Toolless mounting HW – Center to Center	1248mm(vertical mounting bracket included)
Product Warranty	Standard 1 year warranty

## Product Specification and Options

### System Features

<b>Certification/Agency Approvals</b>	CE Marked
<b>Certification/Agency Approvals</b>	FCC Marked
<b>Certification/Agency Approvals</b>	Complies with IEC 62368-1
<b>Certification/Agency Approvals</b>	Complies with EN 55032 and EN 55035
<b>Certification/Agency Approvals</b>	RoHS
<b>Chassis Dimensions (LxWxD)</b>	1500mm x 65.5mm x 45mm
<b>Shipped Weight</b>	4.5kg